

STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAOTRANSITION ALTITUDE
11 000 FTMIRI/MIRI (WBGR)
RWY 20
RNAV (GNSS)ASAKI 1B AROVU 1B BEVDO 1B
BIPAS 1B DOXES 1B DUGEV 1B
ESLAB 1B EXUGO1B GODOM 1B

DUGEV 1B DEPARTURE FOR ROUTE W446

| NO. | PATH TERMINATOR | WAYPOINT IDENTIFIER | FLY OVER | COURSE/TRACK °M | DISTANCE (NM) | TURN DIRECTION | ALTITUDE CONSTRAINT | SPEED LIMIT (KT) | NAV SPEC |
|-----|-----------------|---------------------|----------|-----------------|---------------|----------------|---------------------|------------------|----------|
| 010 | CA | RWY20 | - | 205° | - | - | 1500 | - | - |
| 020 | DF | ADNOX | - | - | - | - | - | - | RNAV1 |
| 030 | TF | DUGEV | - | 203° | 24.0 | - | 7000 | - | RNAV1 |

GODOM 1B DEPARTURE FOR ROUTE G580 EASTBOUND

| NO. | PATH TERMINATOR | WAYPOINT IDENTIFIER | FLY OVER | COURSE/TRACK °M | DISTANCE (NM) | TURN DIRECTION | ALTITUDE CONSTRAINT | SPEED LIMIT (KT) | NAV SPEC |
|-----|-----------------|---------------------|----------|-----------------|---------------|----------------|---------------------|------------------|----------|
| 010 | CA | RWY20 | - | 205° | - | - | 2200 | - | - |
| 020 | DF | DOSNA | - | - | - | L | - | - | RNAV1 |
| 030 | TF | GODOM | - | 028° | 11.4 | L | 7000 | - | RNAV1 |

MINIMUM CLIMB GRADIENT (PDG) 5.0% UNTIL PASSING 7000 FT DUE TO AIRWAY OVER LIMIT

EXUGO 1B DEPARTURE FOR ROUTE W450

| NO. | PATH TERMINATOR | WAYPOINT IDENTIFIER | FLY OVER | COURSE/TRACK °M | DISTANCE (NM) | TURN DIRECTION | ALTITUDE CONSTRAINT | SPEED LIMIT (KT) | NAV SPEC |
|-----|-----------------|---------------------|----------|-----------------|---------------|----------------|---------------------|------------------|----------|
| 010 | CA | RWY20 | - | 205° | - | - | 2200 | - | - |
| 020 | DF | DOSNA | - | - | - | L | - | - | RNAV1 |
| 030 | TF | EXUGO | - | 036° | 10.7 | L | 5000 | - | RNAV1 |

MINIMUM CLIMB GRADIENT (PDG) 5.0% UNTIL PASSING 5000 FT DUE TO AIRWAY OVER LIMIT

ESLAB 1B DEPARTURE FOR ROUTE W449

| NO. | PATH TERMINATOR | WAYPOINT IDENTIFIER | FLY OVER | COURSE/TRACK °M | DISTANCE (NM) | TURN DIRECTION | ALTITUDE CONSTRAINT | SPEED LIMIT (KT) | NAV SPEC |
|-----|-----------------|---------------------|----------|-----------------|---------------|----------------|---------------------|------------------|----------|
| 010 | CA | RWY20 | - | 205° | - | - | 2200 | - | - |
| 020 | DF | ESLAB | - | - | - | L | 5000 | - | RNAV1 |

MINIMUM CLIMB GRADIENT (PDG) 5.0% UNTIL PASSING 5000 FT DUE TO AIRWAY OVER LIMIT

CHANGES : REMOVE THE SPEED LIMIT (KT) IN TABULAR.