

STANDARD ARRIVAL CHART
INSTRUMENT (STAR) - ICAO

TRANSITION ALTITUDE
11,000 FT

KOTA KINABALU / KOTA KINABALU
(WBKK)
RWY 20
ARRIVALS (EAST)
(RNAV 1)

TABULAR DESCRIPTION

ROUTE DESIGNATOR	SERIAL NUMBER	PATH DESCRIPTOR	WP IDENTIFIER	FLY OVER	COURSE/ °M(°T)	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED (KT) IAS MAX	NAVIGATION SPECIFICATION
ELADO 2A	010	IF	ELADO	-	-	-	-	-	- FL270 + FL140	-	RNAV 1
	020	TF	DUMUB	-	023°	-	38.1	R	- FL150 +9000	-	RNAV 1
	030	TF	DOMBU	-	023°	-	20	-	- 7500 + 5000	185	RNAV 1
	040	TF	NULTO	-	292°	-	10	L	+ 3700	185	RNAV 1
	050	TF	LANEK	-	203°	-	4.5	L	2300	185	RNAV 1
VETAG 1A	010	IF	VETAG	-	-	-	-	-	- FL150 + 9000	-	RNAV 1
	020	TF	AKNIR	-	231°	-	10.6	R	- FL130 + 7500	-	RNAV 1
	030	TF	NULTO	-	218°	-	20.8	L	+ 3700	185	RNAV 1
	040	TF	LANEK	-	203°	-	4.5	L	2300	185	RNAV 1
KABDU 1A	010	IF	KABDU	-	-	-	-	-	- FL150 + 9000	-	RNAV 1
	020	TF	AKNIR	-	244°	-	11.6	R	- FL130 + 7500	-	RNAV 1
	030	TF	NULTO	-	218°	-	20.8	L	+3700	185	RNAV 1
	040	TF	LANEK	-	203°	-	4.5	L	2300	185	RNAV 1
ANLOD 2A	010	IF	ANLOD	-	-	-	-	-	- FL190 + FL130	-	RNAV 1
	020	TF	GORKA	-	270°	-	20	-	- FL130 + 10000	-	RNAV 1
	030	TF	DOMBU	-	347°	-	14.5	R	- 7500 + 5000	-	RNAV 1
	040	TF	NULTO	-	292°	-	10	L	+3700	185	RNAV 1
	050	TF	LANEK	-	203°	-	4.5	L	2300	185	RNAV 1
TUSVU 1A	010	IF	TUSVU	-	-	-	-	-	- FL200 + 11000	-	RNAV 1
	020	TF	GORKA	-	310°	-	22	R	- FL130 + 10000	-	RNAV 1
	030	TF	DOMBU	-	347°	-	14.5	R	- 7500 + 5000	-	RNAV 1
	040	TF	NULTO	-	292°	-	10	L	+3700	185	RNAV 1
	050	TF	LANEK	-	203°	-	4.5	L	2300	185	RNAV 1
MAKSU 2A	010	IF	MAKSU	-	-	-	-	-	- FL220 + 11000	-	RNAV 1
	020	TF	GORKA	-	334°	-	27	R	- FL130 + 10000	-	RNAV 1
	030	TF	DOMBU	-	347°	-	14.5	R	- 7500 + 5000	-	RNAV 1
	040	TF	NULTO	-	292°	-	10	L	+ 3700	185	RNAV 1
	050	TF	LANEK	-	203°	-	4.5	L	2300	185	RNAV 1

CHANGES : AT ANLOD 2A, TUSVU 1A & MAKSU 2A TABULAR CHANGE GORKA ALTITUDE TO -FL 130,
AT VETAG 1A & KABDU 1A TABULAR CHANGE AKNIR ALTITUDE TO -FL 130.