

STANDARD ARRIVAL CHART
INSTRUMENT (STAR) - ICAO

TRANSITION ALTITUDE
11 000 FT

KOTA KINABALU/KOTA KINABALU
(WBKK)
RWY 02
ARRIVALS (EAST)
(RNAV 1)

TABULAR DESCRIPTION

ROUTE DESIGNATOR	SERIAL NUMBER	PATH DESCRIPTOR	WP IDENTIFIER	FLY OVER	COURSE/ °M(°T)	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED (KT) IAS MAX	NAVIGATION SPECIFICATION
ENBAX 1B	010	IF	ENBAX	-	-	-	-	-	-	-	RNAV 1
	020	TF	SUSGA	-	162°	-	40	-	- FL210 + FL130	-	RNAV 1
	030	TF	DOGVU	-	203°	-	36.6	R	- 8000 +7000	-	RNAV 1
	040	TF	BIMUM	-	293°	-	12	R	+3900	185	RNAV 1
	050	TF	ADMUS	-	022°	-	4	R	+2700	185	RNAV 1
VETAG 1B	010	IF	VETAG	-	-	-	-	-	- FL210 + FL130	-	RNAV 1
	020	TF	SUSGA	-	204°	-	31.9	L	- FL210 + FL130	-	RNAV 1
	030	TF	DOGVU	-	203°	-	36.6	R	- 8000 +7000	-	RNAV 1
	040	TF	BIMUM	-	293°	-	12	R	+3900	185	RNAV 1
	050	TF	ADMUS	-	022°	-	4	R	+2700	185	RNAV 1
KABDU 1B	010	IF	KABDU	-	-	-	-	-	- FL210 + FL130	-	RNAV 1
	020	TF	SUSGA	-	209°	-	31.5	L	- FL210 + FL130	-	RNAV 1
	030	TF	DOGVU	-	203°	-	36.6	R	- 8000 +7000	-	RNAV 1
	040	TF	BIMUM	-	293°	-	12	R	+3900	185	RNAV 1
	050	TF	ADMUS	-	022°	-	4	R	+2700	185	RNAV 1
ANLOD 2B	010	IF	ANLOD	-	-	-	-	-	- FL190 +FL130	-	RNAV 1
	020	TF	EKUBU	-	241°	-	24	-	-FL140 +11000	-	RNAV 1
	030	TF	DOGVU	-	241°	-	16	-	- 8000 +7000	-	RNAV 1
	040	TF	BIMUM	-	293°	-	12	R	+3900	185	RNAV 1
	050	TF	ADMUS	-	022°	-	4	R	+2700	185	RNAV 1
TUSVU 1B	010	IF	TUSVU	-	-	-	-	-	- FL200 +FL130	-	RNAV 1
	020	TF	EMRUS	-	261°	-	16.8	-	- FL140 +11000	-	RNAV 1
	030	TF	DOGVU	-	261°	-	16	-	- 8000 +7000	-	RNAV 1
	040	TF	BIMUM	-	293°	-	12	R	+3900	185	RNAV 1
	050	TF	ADMUS	-	022°	-	4	R	+2700	185	RNAV 1
MAKSU 2B	010	IF	MAKSU	-	-	-	-	-	- FL220 + FL140	-	RNAV 1
	020	TF	SAPTU	-	280°	-	11.4	-	- FL140 +11000	-	RNAV 1
	030	TF	DOGVU	-	280°	-	16	-	- 8000 +7000	-	RNAV 1
	040	TF	BIMUM	-	293°	-	12	R	+3900	185	RNAV 1
	050	TF	ADMUS	-	022°	-	4	R	+2700	185	RNAV 1

CHANGES : UPDATING THE CHART FORMAT