

STANDARD ARRIVAL CHART
INSTRUMENT (STAR) – ICAOTRANSITION ALT
11000 FTTWR/APP
122.30 (P)
119.25 (S)
121.5

SMC 121.8

ATIS 127.8

BINTULU/BINTULU (WBGB)
RWY35

ARRIVALS (RNP 1)

Serial Number	Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Distance (NM)	Turn Direction	ALT (FT)	Speed Limit (KT)	Recommended Navaid	VPA/TCH	Navigation Specification
ADGAB 3B											
010	IF	ADGAB	-	-	-	-	+FL110	-	-	-	RNP 1
020	TF	SUKOD	-	128.0°(128.5°)	20.4	-	+5500	-	-	-	RNP 1
030	TF	BUDVA	-	090.°(90.4°)	7.6	L	+3200	250	-	-	RNP 1
040	TF	IBEMA	-	057°(057.6°)	5	L	+2000	250	-	-	RNP 1
BASUV 3B											
010	IF	BASUV	-	-	-	-	+7000	-	-	-	RNP 1
020	TF	SUKOD	-	086.3°(086.8°)	9.8	-	+5500	250	-	-	RNP 1
030	TF	BUDVA	-	090.°(90.4°)	7.6	-	+3200	250	-	-	RNP 1
040	TF	IBEMA	-	057°(057.6°)	5.0	L	+2000	220	-	-	RNP 1
BENLI 3B											
010	IF	BENLI	-	-	-	-	+7000	-	-	-	RNP 1
020	TF	SUKOD	-	048.7°(048.9°)	24.7	-	+5500	250	-	-	RNP 1
030	TF	BUDVA	-	090.°(90.4°)	7.6	R	+3200	220	-	-	RNP 1
040	TF	IBEMA	-	057°(057.6°)	5.0	L	+2000	-	-	-	RNP 1
NOKER 3B											
010	IF	NOKER	-	-	-	-	+10000	-	-	-	RNP 1
020	TF	KASPA	-	243.5°(244.0°)	15.0	-	+7000	250	-	-	RNP 1
030	TF	AVLER	-	182.7°(183.2°)	18.6	L	+3200	250	-	-	RNP 1
040	TF	IBEMA	-	277.1°(277.6°)	5.0	R	+2000	220	-	-	RNP 1
EKETO 3B											
010	IF	EKETO	-	-	-	-	+11000	-	-	-	RNP 1
020	TF	KASPA	-	205.2°(205.6°)	16.4	-	+7000	250	-	-	RNP 1
030	TF	AVLER	-	182.7°(183.2°)	18.6	L	+3200	250	-	-	RNP 1
040	TF	IBEMA	-	277.1°(277.6°)	5	R	+2000	220	-	-	RNP 1
DUNAS 3B											
010	IF	DUNAS	-	-	-	-	+10000	-	-	-	RNP 1
020	TF	KASPA	-	215.8°(216.3°)	15.7	-	+7000	250	-	-	RNP 1
030	TF	AVLER	-	182.7°(183.2°)	18.6	L	+3200	250	-	-	RNP 1
040	TF	IBEMA	-	277.1°(277.6°)	5	R	+2000	220	-	-	RNP 1