

**STANDARD DEPARTURE CHART  
INSTRUMENT (SID) - ICAO**

TRANSITION ALTITUDE 11 000 FT
----------------------------------

**MIRI/MIRI (WBGR)  
RWY 02  
RNAV (GNSS)**

ASAKI 1A AROVU 1A BEVDO 1A  
BIPAS 1A DOXES 1A DUGEV 1A  
ESLAB 1A EXUGO 1A GODOM 1A

**DUGEV 1A DEPARTURE FOR ROUTE W446**

NO.	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE/TRACK °M	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	NAV SPEC
010	CA	RWY02	-	025°	-	-	<u>1500</u>	-	-
020	DF	BETNA	-	-	-	L	-	-	RNAV1
030	TF	DUGEV	-	189°	29.0	L	<u>7000</u>	-	RNAV1

**GODOM 1A DEPARTURE FOR ROUTE G580 NORTHBOUND**

NO.	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE/TRACK °M	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	NAV SPEC
010	CA	RWY02	-	025°	-	-	<u>1500</u>	-	-
020	DF	GODOM	-	-	-	R	<u>7000</u>	-	RNAV1

**MINIMUM CLIMB GRADIENT (PDG) 5.0% UNTIL 7000 FT DUE TO CTR.**

**EXUGO 1A DEPARTURE FOR ROUTE W450**

NO.	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE/TRACK °M	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	NAV SPEC
010	CA	RWY02	-	025°	-	-	<u>1500</u>	-	-
020	DF	EXUGO	-	-	-	R	<u>5000</u>	-	RNAV1

**MINIMUM CLIMB GRADIENT (PDG) 5.0% UNTIL 5000 FT DUE TO CTR.**

**ESLAB 1A DEPARTURE FOR ROUTE W449**

NO.	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE/TRACK °M	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	NAV SPEC
010	CA	RWY02	-	025°	-	-	<u>1500</u>	-	-
020	DF	ESLAB	-	-	-	R	<u>5000</u>	-	RNAV1

**MINIMUM CLIMB GRADIENT (PDG) 5.0% UNTIL 5000 FT DUE TO CTR.**