

STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO

TRANSITION ALTITUDE
 11000FT

SUBANG/SULTAN ABDUL
AZIZ SHAH (WMSA)
RNAV RWY 15
 BIKDU 3L PIBOS 3L RUSBU 3L
 MITOS 3L SALAX 3L PUGER 3L
 IBUKU 3L ATIMU 3L

TABULAR DESCRIPTION

SALAX THREE LIMA DEPARTURE (SALAX 3L)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (M)	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	SA641	-	150°	-	5.0	-	-	-	RNAV 1
TF	SA644	-	060°	-	5.5	L	+2500	-210	RNAV 1
TF	SA645	-	060°	-	4.5	-	-	-	RNAV 1
TF	SA636	-	124°	-	13.9	R	-	-	RNAV 1
TF	SA638	-	150°	-	22.4	R	-	-	RNAV 1
TF	SA639	-	150°	-	8.2	-	-	-	RNAV 1
TF	DUMOK	-	217°	-	19.4	R	-	-	RNAV 1
TF	SALAX	-	258°	-	27.0	R	-	-	RNAV 1

MINIMUM CLIMB GRADIENT (PDG) 5.5% UNTIL SA644 DUE TO OBSTACLE.

PUGER THREE LIMA DEPARTURE (PUGER 3L)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (M)	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	SA641	-	150°	-	5.0	-	-	-	RNAV 1
TF	SA642	-	240°	-	8.0	R	@2500	-210	RNAV 1
TF	SA643	-	274°	-	12.0	R	-	-	RNAV 1
TF	SADGI	-	274°	-	10.6	-	-	-	RNAV 1
TF	RUPDO	-	331°	-	15.9	R	-	-	RNAV 1
TF	PUGER	-	284°	-	42.4	L	-	-	RNAV 1

MINIMUM CLIMB GRADIENT (PDG) 5.5% UNTIL 2500FT DUE TO OBSTACLE.

IBUKU THREE LIMA DEPARTURE (IBUKU 3L)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (M)	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	SA641	-	150°	-	5.0	-	-	-	RNAV 1
TF	SA642	-	240°	-	8.0	R	@2500	-210	RNAV 1
TF	SA643	-	274°	-	12.0	R	-	-	RNAV 1
TF	SADGI	-	274°	-	10.6	-	-	-	RNAV 1
TF	RUPDO	-	331°	-	15.9	R	-	-	RNAV 1
TF	IBUKU	-	331°	-	24.5	-	-	-	RNAV 1

MINIMUM CLIMB GRADIENT (PDG) 5.5% UNTIL 2500FT DUE TO OBSTACLE.

ATIMU THREE LIMA DEPARTURE (ATIMU 3L)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (M)	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	SA641	-	150°	-	5.0	-	-	-	RNAV 1
TF	SA642	-	240°	-	8.0	R	@2500	-210	RNAV 1
TF	SA643	-	274°	-	12.0	R	-	-	RNAV 1
TF	SADGI	-	274°	-	10.6	-	-	-	RNAV 1
TF	RUPDO	-	331°	-	15.9	R	-	-	RNAV 1
TF	ATIMU	-	360°	-	26.1	R	-	-	RNAV 1

MINIMUM CLIMB GRADIENT (PDG) 5.5% UNTIL 2500FT DUE TO OBSTACLE.