

TRANSITION ALTITUDE  
11000 FT

PUGER 2M NIREN 2M KAKAK 2M  
PULIP 2M SAROX 2M GUPTA 2M  
SALAX 2M

**TABULAR DESCRIPTION**

**PUGER TWO MIKE ARRIVAL (PUGER 2M)**

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (M)	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	PUGER	-	-	-	-	-	-	-	RNAV1
TF	BORDU	-	095°	-	36.3	-	-	-	RNAV1
TF	SA601	-	060°	-	37.3	L	-	-	RNAV1
TF	SA602	-	150°	-	5.0	R	-	-	RNAV1
TF	SA603	-	150°	-	5.0	-	+ 8000	-	RNAV1
TF	SA604	-	150°	-	5.0	-	-	-	RNAV1
TF	SA605	-	150°	-	4.5	-	-	- 230	RNAV1
TF	SA606	-	240°	-	5.0	R	-	-	RNAV1
TF	SA607	-	330°	-	4.5	R	-	-	RNAV1
TF	SA608	-	330°	-	5.0	-	-	- 210	RNAV1
TF	SA609	-	330°	-	5.0	-	-	-	RNAV1
TF	SA610	-	240°	-	5.0	L	-	-	RNAV1
TF	SA611	-	150°	-	5.0	L	+ 4000	-	RNAV1

**NIREN TWO MIKE ARRIVAL (NIREN 2M)**

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (M)	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	NIREN	-	-	-	-	-	-	-	RNAV1
TF	BORDU	-	114°	-	22.7	-	-	-	RNAV1
TF	SA601	-	060°	-	37.3	L	-	-	RNAV1
TF	SA602	-	150°	-	5.0	R	-	-	RNAV1
TF	SA603	-	150°	-	5.0	-	+ 8000	-	RNAV1
TF	SA604	-	150°	-	5.0	-	-	-	RNAV1
TF	SA605	-	150°	-	4.5	-	-	- 230	RNAV1
TF	SA606	-	240°	-	5.0	R	-	-	RNAV1
TF	SA607	-	330°	-	4.5	R	-	-	RNAV1
TF	SA608	-	330°	-	5.0	-	-	- 210	RNAV1
TF	SA609	-	330°	-	5.0	-	-	-	RNAV1
TF	SA610	-	240°	-	5.0	L	-	-	RNAV1
TF	SA611	-	150°	-	5.0	L	+ 4000	-	RNAV1