

**STANDARD ARRIVAL CHART
INSTRUMENT (STAR) - ICAO****SUBANG/SULTAN ABDUL
AZIZ SHAH (WMSA)
RNAV RWY 15**TRANSITION ALTITUDE
11000 FTPUGER 2M NIREN 2M KAKAK 2M
PULIP 2M SAROX 2M GUPTA 2M
SALAX 2M**KAKAK TWO MIKE ARRIVAL (KAKAK 2M)**

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (M)	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	KAKAK	-	-	-	-	-	-	-	RNAV1
TF	SA601	-	118°	-	13.6	-	-	-	RNAV1
TF	SA602	-	150°	-	5.0	R	-	-	RNAV1
TF	SA603	-	150°	-	5.0	-	+ 8000	-	RNAV1
TF	SA604	-	150°	-	5.0	-	-	-	RNAV1
TF	SA605	-	150°	-	4.5	-	-	- 230	RNAV1
TF	SA606	-	240°	-	5.0	R	-	-	RNAV1
TF	SA607	-	330°	-	4.5	R	-	-	RNAV1
TF	SA608	-	330°	-	5.0	-	-	- 210	RNAV1
TF	SA609	-	330°	-	5.0	-	-	-	RNAV1
TF	SA610	-	240°	-	5.0	L	-	-	RNAV1
TF	SA611	-	150°	-	5.0	L	+ 4000	-	RNAV1

PULIP TWO MIKE ARRIVAL (PULIP 2M)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (M)	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	PULIP	-	-	-	-	-	-	-	RNAV1
TF	SA603	-	248°	-	24.7	-	+ 8000	-	RNAV1
TF	SA604	-	150°	-	5.0	L	-	-	RNAV1
TF	SA605	-	150°	-	4.5	-	-	- 230	RNAV1
TF	SA606	-	240°	-	5.0	R	-	-	RNAV1
TF	SA607	-	330°	-	4.5	R	-	-	RNAV1
TF	SA608	-	330°	-	5.0	-	-	- 210	RNAV1
TF	SA609	-	330°	-	5.0	-	-	-	RNAV1
TF	SA610	-	240°	-	5.0	L	-	-	RNAV1
TF	SA611	-	150°	-	5.0	L	+ 4000	-	RNAV1