

**STANDARD ARRIVAL CHART
INSTRUMENT (STAR) - ICAO****SUBANG/SULTAN ABDUL
AZIZ SHAH (WMSA)****RNAV RWY 15**TRANSITION ALTITUDE
11000 FTPUGER 2M NIREN 2M KAKAK 2M
PULIP 2M SAROX 2M GUPTA 2M
SALAX 2M**SAROX TWO MIKE ARRIVAL (SAROX 2M)**

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (M)	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	SAROX	-	-	-	-	-	-	-	RNAV1
TF	SA624	-	243°	-	32.4	-	-	-	RNAV1
TF	SA622	-	279	-	20.0	R	-	-	RNAV1
TF	SA621	-	314	-	10.3	R	-	-	RNAV1
TF	SA620	-	345°	-	29.1	R	+ 7000	- 230	RNAV1
TF	SA606	-	330°	-	10.0	L	-	-	RNAV1
TF	SA607	-	330°	-	4.5	-	-	-	RNAV1
TF	SA608	-	330°	-	5.0	-	-	- 210	RNAV1
TF	SA609	-	330°	-	5.0	-	-	-	RNAV1
TF	SA610	-	240°	-	5.0	L	-	-	RNAV1
TF	SA611	-	150°	-	5.0	L	+ 4000	-	RNAV1

GUPTA TWO MIKE ARRIVAL (GUPTA 2M)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (M)	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	GUPTA	-	-	-	-	-	-	-	RNAV1
TF	SA623	-	292°	-	36.1	-	-	-	RNAV1
TF	SA622	-	314°	-	18.5	R	-	-	RNAV1
TF	SA621	-	314°	-	10.3	-	-	-	RNAV1
TF	SA620	-	345°	-	29.1	R	+ 7000	- 230	RNAV1
TF	SA606	-	330°	-	10.0	L	-	-	RNAV1
TF	SA607	-	330°	-	4.5	-	-	-	RNAV1
TF	SA608	-	330°	-	5.0	-	-	- 210	RNAV1
TF	SA609	-	330°	-	5.0	-	-	-	RNAV1
TF	SA610	-	240°	-	5.0	L	-	-	RNAV1
TF	SA611	-	150°	-	5.0	L	+ 4000	-	RNAV1