

**STANDARD ARRIVAL CHART
INSTRUMENT (STAR) - ICAO**

**ALOR SETAR/
SULTAN ABDUL HALIM (WMKA)
RNAV (GNSS) RWY 04**

TRANSITION ALTITUDE
11000 FT

PAYAR 1E JERAI 1E TAMOS 1E
 KARMI 1E MULOT 1E

TABULAR DESCRIPTION

JERAI 1E ARRIVAL

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE/TRACK (°M)	DISTANCE NM	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	RECOMMENDED NAVAIDS	NAVIGATION SPECIFICATION
IF	OMBUL	-	-	-	-	+7000	-	-	RNAV 1
TF	JERAI	-	008°	8.0	-	-	-	-	RNAV 1
TF	BUVDU	-	328°	5.1	L	+3500	-	-	RNAV 1
TF	OLTIP (IAF)	-	332°	5.0	-	+2500	-	-	RNAV 1

MULOT 1E ARRIVAL

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE/TRACK (°M)	DISTANCE NM	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	RECOMMENDED NAVAIDS	NAVIGATION SPECIFICATION
IF	MULOT	-	-	-	-	+5000	-	-	RNAV 1
TF	UDUTA	-	087°	5.8	-	-	-	-	RNAV 1
TF	ESMIR	-	125°	8.8	R	+3500	-	-	RNAV 1
TF	OLTIP (IAF)	-	112°	5.0	-	+2500	-	-	RNAV 1

PAYAR 1E ARRIVAL

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE/TRACK (°M)	DISTANCE NM	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	RECOMMENDED NAVAIDS	NAVIGATION SPECIFICATION
IF	VPG	-	-	-	-	+7000	-	-	RNAV 1
TF	PAYAR	-	355°	41.8	-	+3500	-	-	RNAV 1
TF	OLTIP (IAF)	-	042°	6.0	R	+2500	-	-	RNAV 1

TAMOS 1E ARRIVAL

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE/TRACK (°M)	DISTANCE NM	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	RECOMMENDED NAVAIDS	NAVIGATION SPECIFICATION
IF	TAMOS	-	-	-	-	+7000	-	-	RNAV 1
TF	BIDAL	-	199°	19.9	-	+3500	-	-	RNAV 1
TF	ESMIR	-	214°	9.6	-	+3500	-	-	RNAV 1
TF	OLTIP (IAF)	-	112°	5.0	L	+2500	-	-	RNAV 1

KARMI 1E ARRIVAL

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE/TRACK (°M)	DISTANCE NM	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	RECOMMENDED NAVAIDS	NAVIGATION SPECIFICATION
IF	KARMI	-	-	-	-	+10500	-	-	RNAV 1
TF	BIDAL	-	220°	21.9	-	+3500	-	-	RNAV 1
TF	ESMIR	-	214°	9.6	-	+3500	-	-	RNAV 1
TF	OLTIP (IAF)	-	112°	5.0	L	+2500	-	-	RNAV 1