

STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO

TRANSITION ALTITUDE
 11000 FT

SEPANG/KL INTERNATIONAL
AIRPORT (WMKK)
RNAV (GNSS) RWY 14R

PUGER 1B BIKDU 1B SALAX 1B
 IBUKU 1B PIBOS 1B MITOS 1B
 ATIMU 1B KIMAT 1B RUSBU 1B

IBUKU ONE BRAVO DEPARTURE (IBUKU 1B)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK720	-	146	-	12.9	-	-	-	RNP 1
TF	OLKAN	-	236	-	8.2	R	+6000	-	RNP 1
TF	KK721	-	326	-	13.2	R	+10000	-	RNP 1
TF	MATPO	-	311	-	18.7	L	-	-	RNP 1
TF	SADGI	-	301	-	18.1	L	-	-	RNP 1
TF	RUPDO	-	331	-	15.9	R	-	-	RNP 1
TF	IBUKU	-	331	-	24.5	-	-	-	RNP 1

ATIMU ONE BRAVO DEPARTURE (ATIMU 1B)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK720	-	146	-	12.9	-	-	-	RNP 1
TF	OLKAN	-	236	-	8.2	R	+6000	-	RNP 1
TF	KK721	-	326	-	13.2	R	+10000	-	RNP 1
TF	MATPO	-	311	-	18.7	L	-	-	RNP 1
TF	SADGI	-	301	-	18.1	L	-	-	RNP 1
TF	RUPDO	-	331	-	15.9	R	-	-	RNP 1
TF	ATIMU	-	360	-	26.1	R	-	-	RNP 1

BIKDU ONE BRAVO DEPARTURE (BIKDU 1B)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK720	-	146	-	12.9	-	-	-	RNP 1
TF	KK719	-	064	-	19.3	L	-	-	RNP 1
TF	LALUT	-	048	-	13.5	L	-	-	RNP 1
TF	PIBOS	-	335	-	34.5	L	-	-	RNP 1
TF	BIKDU	-	308	-	48.1	L	-	-	RNP 1

KIMAT ONE BRAVO DEPARTURE (KIMAT 1B)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK720	-	146	-	12.9	-	-	-	RNP 1
TF	KK719	-	064	-	19.3	L	-	-	RNP 1
TF	LALUT	-	048	-	13.5	L	-	-	RNP 1
TF	KIMAT	-	009	-	20.2	L	-	-	RNP 1

CHANGES: CHANGE DISTANCE FOR PIBOS & BIKDU