

STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO

TRANSITION ALTITUDE
 11000 FT

SEPANG/KL INTERNATIONAL
AIRPORT (WMKK)
RNAV (GNSS) RWY 32L

PUGER 1E BIKDU 1E SALAX 1E
 IBUKU 1E PIBOS 1E MITOS 1E
 ATIMU 1E KIMAT 1E RUSBU 1E

IBUKU ONE ECHO DEPARTURE (IBUKU 1E)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK707	Y	326	-	1.1		-	-	RNP 1
TF	KK708	-	310	-	10.4	-	-	-	RNP 1
TF	GUTIK	-	324	-	19.8	R	-	-	RNP 1
TF	IBUKU	-	308	-	44.2	L	-	-	RNP 1

PUGER ONE ECHO DEPARTURE (PUGER 1E)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK707	Y	326	-	1.1		-	-	RNP 1
TF	KK708	-	310	-	10.4	-	-	-	RNP 1
TF	GUTIK	-	324	-	19.8	R	-	-	RNP 1
TF	RUPDO	-	284	-	23.6	L	-	-	RNP 1
TF	PUGER	-	284	-	42.4	-	-	-	RNP 1

ATIMU ONE ECHO DEPARTURE (ATIMU 1E)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK707	Y	326	-	1.1		-	-	RNP 1
TF	KK708	-	310	-	10.4	-	-	-	RNP 1
TF	GUTIK	-	324	-	19.8	R	-	-	RNP 1
TF	ATIMU	-	324	-	39.1	-	-	-	RNP 1

BIKDU ONE ECHO DEPARTURE (BIKDU 1E)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK707	Y	326	-	1.1		-	-	RNP 1
TF	KK708	-	310	-	10.4	-	-	-	RNP 1
TF	GUTIK	-	324	-	19.8	R	-	-	RNP 1
TF	BIKDU	-	005	-	42.1	R	-	-	RNP 1

CHANGES: CHANGE DISTANCE FOR PUGER.