

**STANDARD ARRIVAL CHART  
INSTRUMENT (STAR) - ICAO**

TRANSITION ALTITUDE  
11 000 FT

**BINTULU/BINTULU (WBGB)  
ARRIVALS RWY 17 (RNP 1)**

ADGAB 3A EKETO 3A  
BASUV 3A DUNAS 3A  
BENLI 3A NOKER 3A

**TABULAR DESCRIPTION**

**ADGAB 3A**

SERIAL NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M(°T)	DISTANCE (NM)	TURN DIRECTION	ALT (FT)	SPEED LIMIT (KT)	RECOM-MENDED NAVAID	VPA/TCH	NAGIVATION SPECIFICATION
010	IF	ADGAB	-	-	-	-	+8000	250	-	-	RNP 1
020	TF	IRTUX	-	081.5°(082°)	17.2	-	+5000	250	-	-	RNP 1
030	TF	MESUT	-	003.6°(004°)	10.9	L	+2700	250	-	-	RNP 1
040	TF	ELAMI	-	097.1°(097.6°)	5.0	R	+1700	220	-	-	RNP 1

**BASUV 3A**

SERIAL NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M(°T)	DISTANCE (NM)	TURN DIRECTION	ALT (FT)	SPEED LIMIT (KT)	RECOM-MENDED NAVAID	VPA/TCH	NAGIVATION SPECIFICATION
010	IF	BASUV	-	-	-	-	+8000	-	-	-	RNP 1
020	TF	GB507	-	047.3°(047.8°)	14.0	-	+6000	250	-	-	RNP 1
030	TF	IRTUX	-	003.5°(004.0°)	6.2	L	+5000	250	-	-	RNP 1
040	TF	MESUT	-	003.5°(004.0°)	10.9	-	+2700	250	-	-	RNP 1
050	TF	ELAMI	-	097.1°(097.6°)	5.0	R	+1700	220	-	-	RNP 1

**BENLI 3A**

SERIAL NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M(°T)	DISTANCE (NM)	TURN DIRECTION	ALT (FT)	SPEED LIMIT (KT)	RECOM-MENDED NAVAID	VPA/TCH	NAGIVATION SPECIFICATION
010	IF	BENLI	-	-	-	-	+9000	-	-	-	RNP 1
020	TF	SUKOD	-	028.3°(028.8°)	6.6	-	+8000	250	-	-	RNP 1
030	TF	GB507	-	003.5°(004.0°)	8.9	L	+6000	250	-	-	RNP 1
040	TF	IRTUX	-	003.5°(004.0°)	6.2	-	+5000	250	-	-	RNP 1
050	TF	MESUT	-	003.5°(004.0°)	10.9	-	+2700	250	-	-	RNP 1
060	TF	ELAMI	-	097.1°(097.6°)	5.0	R	+1700	220	-	-	RNP 1

**EKETO 3A**

SERIAL NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M(°T)	DISTANCE (NM)	TURN DIRECTION	ALT (FT)	SPEED LIMIT (KT)	RECOM-MENDED NAVAID	VPA/TCH	NAGIVATION SPECIFICATION
010	IF	VMY	-	-	-	-	-	-	-	-	RNP 1
020	TF	EKETO	-	219.9°(220.4°)	67.0	-	+7000	250	-	-	RNP 1
030	TF	GB506	-	219.9°(220.4°)	10.0	-	+4000	250	-	-	RNP 1
040	TF	ELPID	-	272.0°(272.4°)	7.4	R	+2700	250	-	-	RNP 1
050	TF	ELAMI	-	237.1°(237.6°)	5.0	L	+1700	220	-	-	RNP 1

**NOKER 3A**

SERIAL NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M(°T)	DISTANCE (NM)	TURN DIRECTION	ALT (FT)	SPEED LIMIT (KT)	RECOM-MENDED NAVAID	VPA/TCH	NAGIVATION SPECIFICATION
010	IF	LOTGA	-	244.0°(244.4°)	-	-	+8000	-	-	-	RNP 1
020	TF	NOKER	-	243.6°(244.0°)	14.0	-	+7000	250	-	-	RNP 1
030	TF	GB506	-	272.0°(272.4°)	12.9	R	+4000	250	-	-	RNP 1
040	TF	ELPID	-	272.0°(272.4°)	7.4	R	+2700	250	-	-	RNP 1
050	TF	ELAMI	-	237.1°(237.6°)	5.0	L	+1700	220	-	-	RNP 1

CHANGES : CHANGE MIRI VMI TO VMY