

**STANDARD ARRIVAL CHART
INSTRUMENT (STAR) - ICAO**

**SUBANG/SULTAN ABDUL
AZIZ SHAH (WMSA)
RNAV 1 (GNSS) RWY 15**

TRANSITION ALTITUDE
11000 FT

PUGER 1M NIREN 1M KAKAK 1M
PULIP 1M SAROX 1M GUPTA 1M
SALAX 1M

KAKAK ONE MIKE ARRIVAL (KAKAK 1M)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	KAKAK	-	-	-	-	-	-	-	RNAV1
TF	SA601	-	118	-	13.6	-	-	-	RNAV1
TF	SA602	-	150	-	5.0	R	-	-	RNAV1
TF	SA603	-	150	-	5.0	-	+ 8000	-	RNAV1
TF	SA604	-	150	-	5.0	-	-	-	RNAV1
TF	SA605	-	150	-	4.5	-	-	- 230	RNAV1
TF	SA606	-	240	-	5.0	R	-	-	RNAV1
TF	SA607	-	330	-	4.5	R	-	-	RNAV1
TF	SA608	-	330	-	5.0	-	-	- 210	RNAV1
TF	SA609	-	330	-	5.0	-	-	-	RNAV1
TF	SA610	-	240	-	5.0	L	-	-	RNAV1
TF	SA611	-	150	-	5.0	L	+ 4000	-	RNAV1
TF	SA612	-	150	-	9.6	-	+ 2500	-	RNAV1

PULIP ONE MIKE ARRIVAL (PULIP 1M)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	PULIP	-	-	-	-	-	-	-	RNAV1
TF	SA603	-	248	-	24.7	-	+ 8000	-	RNAV1
TF	SA604	-	150	-	5.0	L	-	-	RNAV1
TF	SA605	-	150	-	4.5	-	-	- 230	RNAV1
TF	SA606	-	240	-	5.0	R	-	-	RNAV1
TF	SA607	-	330	-	4.5	R	-	-	RNAV1
TF	SA608	-	330	-	5.0	-	-	- 210	RNAV1
TF	SA609	-	330	-	5.0	-	-	-	RNAV1
TF	SA610	-	240	-	5.0	L	-	-	RNAV1
TF	SA611	-	150	-	5.0	L	+ 4000	-	RNAV1
TF	SA612	-	150	-	9.6	-	+ 2500	-	RNAV1

CHANGES: AT WAYPOINT IDENTIFIER CHANGE CE TO SA612