

**STANDARD ARRIVAL CHART  
INSTRUMENT (STAR) - ICAO**

**SUBANG/SULTAN ABDUL  
AZIZ SHAH (WMSA)  
RNAV 1 (GNSS) RWY 15**

TRANSITION ALTITUDE  
11000 FT

PUGER 1M NIREN 1M KAKAK 1M  
PULIP 1M SAROX 1M GUPTA 1M  
SALAX 1M

**SAROX ONE MIKE ARRIVAL (SAROX 1M)**

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	SAROX	-	-	-	-	-	-	-	RNAV1
TF	SA624	-	243	-	32.4	-	-	-	RNAV1
TF	SA622	-	279	-	20.0	R	-	-	RNAV1
TF	SA621	-	314	-	10.3	R	-	-	RNAV1
TF	SA620	-	345	-	29.1	R	+ 7000	- 230	RNAV1
TF	SA606	-	330	-	10.0	L	-	-	RNAV1
TF	SA607	-	330	-	4.5	-	-	-	RNAV1
TF	SA608	-	330	-	5.0	-	-	- 210	RNAV1
TF	SA609	-	330	-	5.0	-	-	-	RNAV1
TF	SA610	-	240	-	5.0	L	-	-	RNAV1
TF	SA611	-	150	-	5.0	L	+ 4000	-	RNAV1
TF	SA612	-	150	-	9.6	-	+ 2500	-	RNAV1

**GUPTA ONE MIKE ARRIVAL (GUPTA 1M)**

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	GUPTA	-	-	-	-	-	-	-	RNAV1
TF	SA623	-	292	-	36.1	-	-	-	RNAV1
TF	SA622	-	314	-	18.5	R	-	-	RNAV1
TF	SA621	-	314	-	10.3	-	-	-	RNAV1
TF	SA620	-	345	-	29.1	R	+ 7000	- 230	RNAV1
TF	SA606	-	330	-	10.0	L	-	-	RNAV1
TF	SA607	-	330	-	4.5	-	-	-	RNAV1
TF	SA608	-	330	-	5.0	-	-	- 210	RNAV1
TF	SA609	-	330	-	5.0	-	-	-	RNAV1
TF	SA610	-	240	-	5.0	L	-	-	RNAV1
TF	SA611	-	150	-	5.0	L	+ 4000	-	RNAV1
TF	SA612	-	150	-	9.6	-	+ 2500	-	RNAV1

CHANGES: AT WAYPOINT IDENTIFIER CHANGE CE TO SA612