

**STANDARD ARRIVAL CHART
INSTRUMENT (STAR) - ICAO**

TRANSITION ALTITUDE
11000 FT

**SEPANG/KL INTERNATIONAL
AIRPORT (WMKK)
RNAV (GNSS) RWY 14L, 14R, 15**

PMS NORTH
PUGER 1K KAKAK 1K SAROX 1K
NIREN 1K PULIP 1K GUPTA 1K
SALAX 1K

TABULAR DESCRIPTION

PUGER ONE KILO ARRIVAL (PUGER 1K)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	PUGER	-	-	-	-	-	-	-	RNP 1
TF	ESDAP	-	116	-	40.2	-	-	-	RNP 1
TF	SADGI	-	116	-	14.4	-	-9000	@230	RNP 1
TF	VARLI	-	044	-	5.0	L	-9000	@230	RNP 1
TF	KK822	-	346	-	5.6	L	-	-	RNP 1
TF	KK823	-	006	-	5.6	R	-	-	RNP 1
TF	KK824	-	026	-	5.6	R	-	-	RNP 1
TF	KK825	-	046	-	5.5	R	-	@230	RNP 1
TF	NUPKU	-	146	-	16.0	R	+5000	@210	RNP 1

NIREN ONE KILO ARRIVAL (NIREN 1K)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	NIREN	-	-	-	-	-	-	-	RNP 1
TF	ESDAP	-	139	-	31.4	-	-	-	RNP 1
TF	SADGI	-	116	-	14.4	L	-9000	@230	RNP 1
TF	VARLI	-	044	-	5.0	L	-9000	@230	RNP 1
TF	KK822	-	346	-	5.6	L	-	-	RNP 1
TF	KK823	-	006	-	5.6	R	-	-	RNP 1
TF	KK824	-	026	-	5.6	R	-	-	RNP 1
TF	KK825	-	046	-	5.5	R	-	@230	RNP 1
TF	NUPKU	-	146	-	16.0	R	+5000	@210	RNP 1

KAKAK ONE KILO ARRIVAL (KAKAK 1K)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	KAKAK	-	-	-	-	-	-	-	RNP 1
TF	DAKBA	-	148	-	22.4	-	-	-	RNP 1
TF	RIKMI	-	245	-	10.3	R	+10000	@230	RNP 1
TF	KK831	-	226	-	5.2	L	-	-	RNP 1
TF	KK832	-	206	-	5.2	L	-	-	RNP 1
TF	KK833	-	186	-	5.2	L	-	-	RNP 1
TF	KK834	-	166	-	5.2	L	-	@230	RNP 1
TF	NUPKU	-	066	-	15.0	L	+5000	@210	RNP 1

CHANGES: CHANGE DISTANCE FOR ESDAP