

TABULAR DESCRIPTION

BIKDU ONE LIMA DEPARTURE (BIKDU 1L)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (°M)	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	SA631	-	150	-	3.5	-	-	-	RNAV 1
TF	SA640	-	064	-	5.5	L	+2500	-210	RNAV 1
TF	SA634	-	064	-	4.6	-	-	-	RNAV 1
TF	SA635	-	359	-	27.8	L	-	-	RNAV 1
TF	BIKDU	-	308	-	23.4	L	-	-	RNAV 1

MINIMUM CLIMB GRADIENT (PDG) 5% UNTIL SA640 DUE TO OBSTACLE.

PIBOS ONE LIMA DEPARTURE (PIBOS 1L)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (°M)	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	SA631	-	150	-	3.5	-	-	-	RNAV 1
TF	SA640	-	064	-	5.5	L	+2500	-210	RNAV 1
TF	SA634	-	064	-	4.6	-	-	-	RNAV 1
TF	PIBOS	-	057	-	22.8	-	-	-	RNAV 1

MINIMUM CLIMB GRADIENT (PDG) 5% UNTIL SA640 DUE TO OBSTACLE.

KIMAT ONE LIMA DEPARTURE (KIMAT 1L)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (°M)	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	SA631	-	150	-	3.5	-	-	-	RNAV 1
TF	SA640	-	064	-	5.5	L	+2500	-210	RNAV 1
TF	SA634	-	064	-	4.6	-	-	-	RNAV 1
TF	SA636	-	125	-	14.6	R	-	-	RNAV 1
TF	SA637	-	069	-	5.6	L	-	-	RNAV 1
TF	KIMAT	-	069	-	21.0	-	-	-	RNAV 1

MINIMUM CLIMB GRADIENT (PDG) 5% UNTIL SA640 DUE TO OBSTACLE.

RUSBU ONE LIMA DEPARTURE (RUSBU 1L)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (°M)	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	SA631	-	150	-	3.5	-	-	-	RNAV 1
TF	SA640	-	064	-	5.5	L	+2500	-210	RNAV 1
TF	SA634	-	064	-	4.6	-	-	-	RNAV 1
TF	SA636	-	125	-	14.6	R	-	-	RNAV 1
TF	SA638	-	150	-	22.4	R	-	-	RNAV 1
TF	SA639	-	150	-	8.2	-	-	-	RNAV 1
TF	RUSBU	-	150	-	37.1	-	-	-	RNAV 1

MINIMUM CLIMB GRADIENT (PDG) 5% UNTIL SA640 DUE TO OBSTACLE.