

## TABULAR DESCRIPTION

### RUSBU ONE ROMEO DEPARTURE (RUSBU 1R)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CA	-	-	210	-	-	+2500	-	-
DF	LAVIG	-	-	-	L	+5000	-	RNAV 1
TF	RUSBU	-	090	15.3	L	+6000	-	RNAV 1

MINIMUM CLIMB GRADIENT (PDG) 4.5% UNTIL PASSING 5000 FT DUE TO OBSTACLE & RESTRICTED AREA UPPER LIMIT.

### OGAKO ONE ROMEO DEPARTURE (OGAKO 1R)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CA	-	-	210	-	-	+2500	-	-
DF	LAVIG	-	-	-	L	+5000	-	RNAV 1
TF	OGAKO	-	103	11.0	L	+6000	-	RNAV 1

MINIMUM CLIMB GRADIENT (PDG) 4.5% UNTIL PASSING 5000 FT DUE TO OBSTACLE & RESTRICTED AREA UPPER LIMIT.

### DOSIK ONE ROMEO DEPARTURE (DOSIK 1R)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CA	-	-	210	-	-	+2500	-	-
DF	DOSIK	-	-	-	-	+7000	-	RNAV 1

MINIMUM CLIMB GRADIENT (PDG) 4.5% UNTIL PASSING 2500 FT DUE TO OBSTACLE.

### SAPAT THREE ROMEO DEPARTURE (SAPAT 3R)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CA	-	-	210	-	-	+1500	-	-
DF	KM501	-	-	-	R	+2500	-	RNAV 1
TF	KM503	-	008	12.9	-	+5000	-	RNAV 1
TF	SAPAT	-	324	9.0	L	+7000	-	RNAV 1

MINIMUM CLIMB GRADIENT (PDG) 4.5% UNTIL PASSING 1500 FT DUE TO OBSTACLE.