

**STANDARD DEPARTURE CHART  
INSTRUMENT (SID) - ICAO**

**LABUAN/LABUAN (WBKL)  
RWY 14 (RNAV 1)**

TRANSITION ALTITUDE  
11,000 FT

LAVED 1R

BRUNEI 1R

LIMBANG 1R

IDATU 1R

NOLOT 1R

**TABULAR DESCRIPTION**

**LAVED 1R**

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY-OVER	Course/ °M(°T)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT(KT)	RECOMMENDED NAVAID	NAVIGATION SPECIFICATION
CA	-	-	146°	-	-	+1500	250	-	RNAV 1
DF	UKIBA	-	-	-	R	+6000	250	-	RNAV 1
TF	LAVED	-	278°	11.6	L	+7000	-	-	RNAV 1
TF	ESBOB	-	276°	10	-	-	-	-	RNAV 1

**BRUNEI 1R**

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY-OVER	Course/ °M(°T)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT(KT)	RECOMMENDED NAVAID	NAVIGATION SPECIFICATION
CA	-	-	146°	-	-	+1500	250	-	RNAV 1
DF	BRU VOR	-	-	-	R	-	-	-	RNAV 1

**LIMBANG 1R**

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY-OVER	Course/ °M(°T)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT(KT)	RECOMMENDED NAVAID	NAVIGATION SPECIFICATION
CA	-	-	146°	-	-	+1500	250	-	RNAV 1
DF	VLG VOR	-	-	-	R	-	-	-	RNAV 1

**IDATU 1R**

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY-OVER	Course/ °M(°T)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT(KT)	RECOMMENDED NAVAID	NAVIGATION SPECIFICATION
CA	-	-	146°	-	-	+1500	250	-	RNAV 1
DF	IDATU	-	-	-	L	+5500	-	-	RNAV 1
TF	LATIL	-	108°	50	R	+9000	-	-	RNAV 1

**NOLOT 1R**

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY-OVER	Course/ °M(°T)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT(KT)	RECOMMENDED NAVAID	NAVIGATION SPECIFICATION
CA	-	-	146°	-	-	+1500	250	-	RNAV 1
DF	NOLOT	-	-	-	L	+6000	-	-	RNAV 1
TF	VJN VOR	-	052°	42	R	-	-	-	RNAV 1

**WAYPOINT LIST**

WAYPOINT IDENTIFIER	COORDINATES
NOLOT	05°27'55.70"N 115°28'53.71"E
IDATU	05°09'10.72"N 115°39'10.11"E
ESBOB	05°21'23.69"N 114°40'39.53"E
LAVED	05°20'25.08"N 114°50'36.08"E
BRU	04°52'28.52"N 114°53'07.77"E
VLG	04°47'50.20"N 115°00'08.40"E
VJN	05°53'57.30"N 116°02'02.30"E
LATIL	04°53'40"N 116°26'49"E