

STANDARD ARRIVAL CHART
INSTRUMENT (STAR) - ICAO

BINTULU/BINTULU (WBGB)
ARRIVALS RWY 17 (RNP 1)

TRANSITION ALTITUDE
11 000 FT

ADGAB 3A EKETO 3A
BASUV 3A DUNAS 3A
BENLI 3A NOKER 3A

TABULAR DESCRIPTION

ADGAB 3A

SERIAL NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M(°T)	DISTANCE (NM)	TURN DIRECTION	ALT (FT)	SPEED LIMIT (KT)	RECOMMENDED NAVAID	VPA/TCH	NAGIVATION SPECIFICATION
010	IF	ADGAB	-	-	-	-	+8000	250	-	-	RNP 1
020	TF	IRTUX	-	081.5°(082°)	17.2	-	+5000	250	-	-	RNP 1
030	TF	MESUT	-	003.6°(004°)	10.9	L	+2700	250	-	-	RNP 1
040	TF	ELAMI	-	097.1°(097.6°)	5.0	R	+1700	220	-	-	RNP 1

BASUV 3A

SERIAL NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M(°T)	DISTANCE (NM)	TURN DIRECTION	ALT (FT)	SPEED LIMIT (KT)	RECOMMENDED NAVAID	VPA/TCH	NAGIVATION SPECIFICATION
010	IF	BASUV	-	-	-	-	+8000	-	-	-	RNP 1
020	TF	GB507	-	047.3°(047.8°)	14.0	-	+6000	250	-	-	RNP 1
030	TF	IRTUX	-	003.5°(004.0°)	6.2	L	+5000	250	-	-	RNP 1
040	TF	MESUT	-	003.5°(004.0°)	10.9	-	+2700	250	-	-	RNP 1
050	TF	ELAMI	-	097.1°(097.6°)	5.0	R	+1700	220	-	-	RNP 1

BENLI 3A

SERIAL NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M(°T)	DISTANCE (NM)	TURN DIRECTION	ALT (FT)	SPEED LIMIT (KT)	RECOMMENDED NAVAID	VPA/TCH	NAGIVATION SPECIFICATION
010	IF	BENLI	-	-	-	-	+9000	-	-	-	RNP 1
020	TF	SUKOD	-	028.3°(028.8°)	6.6	-	+8000	250	-	-	RNP 1
030	TF	GB507	-	003.5°(004.0°)	8.9	L	+6000	250	-	-	RNP 1
040	TF	IRTUX	-	003.5°(004.0°)	6.2	-	+5000	250	-	-	RNP 1
050	TF	MESUT	-	003.5°(004.0°)	10.9	-	+2700	250	-	-	RNP 1
060	TF	ELAMI	-	097.1°(097.6°)	5.0	R	+1700	220	-	-	RNP 1

EKETO 3A

SERIAL NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M(°T)	DISTANCE (NM)	TURN DIRECTION	ALT (FT)	SPEED LIMIT (KT)	RECOMMENDED NAVAID	VPA/TCH	NAGIVATION SPECIFICATION
010	IF	VMY	-	-	-	-	-	-	-	-	RNP 1
020	TF	EKETO	-	219.9°(220.4°)	67.0	-	+7000	250	-	-	RNP 1
030	TF	GB506	-	219.9°(220.4°)	10.0	-	+4000	250	-	-	RNP 1
040	TF	ELPID	-	272.0°(272.4°)	7.4	R	+2700	250	-	-	RNP 1
050	TF	ELAMI	-	237.1°(237.6°)	5.0	L	+1700	220	-	-	RNP 1

NOKER 3A

SERIAL NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M(°T)	DISTANCE (NM)	TURN DIRECTION	ALT (FT)	SPEED LIMIT (KT)	RECOMMENDED NAVAID	VPA/TCH	NAGIVATION SPECIFICATION
010	IF	LOTGA	-	244.0°(244.4°)	-	-	+8000	-	-	-	RNP 1
020	TF	NOKER	-	243.6°(244.0°)	14.0	-	+7000	250	-	-	RNP 1
030	TF	GB506	-	272.0°(272.4°)	12.9	R	+4000	250	-	-	RNP 1
040	TF	ELPID	-	272.0°(272.4°)	7.4	R	+2700	250	-	-	RNP 1
050	TF	ELAMI	-	237.1°(237.6°)	5.0	L	+1700	220	-	-	RNP 1

CHANGES : CHANGE MIRI VMI TO VMY