

**STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO**

TRANSITION ALTITUDE 11000 FT

**SEPANG/KL INTERNATIONAL
AIRPORT (WMKK)
RNP 1 (GNSS) RWY 14R**

PUGER 2B BIKDU 2B SALAX 2B
IBUKU 2B PIBOS 2B MITOS 2B
ATIMU 2B KIMAT 2B RUSBU 2B

KIMAT TWO BRAVO DEPARTURE (KIMAT 2B)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK734	-	146	-	7.2	-	-	-	RNP 1
TF	KK733	-	056	-	9.0	L	+3000	-	RNP 1
TF	KIMAT	-	043	-	38.5	-	-	-	RNP 1

RUSBU TWO BRAVO DEPARTURE (RUSBU 2B)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK734	-	146	-	7.2	-	-	-	RNP 1
TF	RUSBU	-	129	-	55.3	-	-	-	RNP 1

MITOS TWO BRAVO DEPARTURE (MITOS 2B)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK734	-	146	-	7.2	-	-	-	RNP 1
TF	MITOS	-	153	-	41.8	R	-	-	RNP 1

SALAX TWO BRAVO DEPARTURE (SALAX 2B)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK734	-	146	-	7.2	-	-	-	RNP 1
TF	KK731	-	236	-	9.0	R	-	-	RNP 1
TF	SALAX	-	199	-	19.7	L	-	-	RNP 1

CHANGES : NEW CHART.