

**STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO**TRANSITION ALTITUDE
11000 FT**SEPANG/KL INTERNATIONAL
AIRPORT (WMKK)
RNAV (GNSS) RWY 14R**PUGER 1B BIKDU 1B SALAX 1B
IBUKU 1B PIBOS 1B MITOS 1B
ATIMU 1B KIMAT 1B RUSBU 1B**IBUKU ONE BRAVO DEPARTURE (IBUKU 1B)**

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK720	-	146	-	12.9	-	-	-	RNP 1
TF	OLKAN	-	236	-	8.2	R	+6000	-	RNP 1
TF	KK721	-	326	-	13.2	R	+10000	-	RNP 1
TF	MATPO	-	311	-	18.7	L	-	-	RNP 1
TF	SADGI	-	301	-	18.1	L	-	-	RNP 1
TF	RUPDO	-	331	-	15.9	R	-	-	RNP 1
TF	IBUKU	-	331	-	24.5	-	-	-	RNP 1

ATIMU ONE BRAVO DEPARTURE (ATIMU 1B)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK720	-	146	-	12.9	-	-	-	RNP 1
TF	OLKAN	-	236	-	8.2	R	+6000	-	RNP 1
TF	KK721	-	326	-	13.2	R	+10000	-	RNP 1
TF	MATPO	-	311	-	18.7	L	-	-	RNP 1
TF	SADGI	-	301	-	18.1	L	-	-	RNP 1
TF	RUPDO	-	331	-	15.9	R	-	-	RNP 1
TF	ATIMU	-	360	-	26.1	R	-	-	RNP 1

BIKDU ONE BRAVO DEPARTURE (BIKDU 1B)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK720	-	146	-	12.9	-	-	-	RNP 1
TF	KK719	-	064	-	19.3	L	-	-	RNP 1
TF	LALUT	-	048	-	13.5	L	-	-	RNP 1
TF	PIBOS	-	335	-	34.5	L	-	-	RNP 1
TF	BIKDU	-	308	-	48.1	L	-	-	RNP 1

KIMAT ONE BRAVO DEPARTURE (KIMAT 1B)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK720	-	146	-	12.9	-	-	-	RNP 1
TF	KK719	-	064	-	19.3	L	-	-	RNP 1
TF	LALUT	-	048	-	13.5	L	-	-	RNP 1
TF	KIMAT	-	009	-	20.2	L	-	-	RNP 1

CHANGES: CHANGE DISTANCE FOR PIBOS & BIKDU