

**STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO**

TRANSITION ALTITUDE
11000 FT

**SEPANG/KL INTERNATIONAL
AIRPORT (WMKK)
RNAV (GNSS) RWY 32L**

PUGER 1E BIKDU 1E SALAX 1E
IBUKU 1E PIBOS 1E MITOS 1E
ATIMU 1E KIMAT 1E RUSBU 1E

TABULAR DESCRIPTION

RUSBU ONE ECHO DEPARTURE (RUSBU 1E)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK707	Y	326	-	1.1	-	-	-	RNP 1
TF	KK708	-	310	-	10.4	-	-	-	RNP 1
TF	KK709	-	310	-	6.4	-	-	-	RNP 1
TF	KK710	-	220	-	7.7	L	+7000	-	RNP 1
TF	KK711	-	130	-	12.2	L	+10000	-	RNP 1
TF	KK712	-	160	-	5.0	R	-	-	RNP 1
TF	IDUMI	-	160	-	17.3	-	-	-	RNP 1
TF	OMBIR	-	135	-	26.7	L	-	-	RNP 1
TF	RUSBU	-	093	-	31.1	L	-	-	RNP 1

MITOS ONE ECHO DEPARTURE (MITOS 1E)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK707	Y	326	-	1.1	-	-	-	RNP 1
TF	KK708	-	310	-	10.4	-	-	-	RNP 1
TF	KK709	-	310	-	6.4	-	-	-	RNP 1
TF	KK710	-	220	-	7.7	L	+7000	-	RNP 1
TF	KK711	-	130	-	12.2	L	+10000	-	RNP 1
TF	KK712	-	160	-	5.0	R	-	-	RNP 1
TF	IDUMI	-	160	-	17.3	-	-	-	RNP 1
TF	OMBIR	-	135	-	26.7	L	-	-	RNP 1
TF	MITOS	-	123	-	7.8	L	-	-	RNP 1

SALAX ONE ECHO DEPARTURE (SALAX 1E)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK707	Y	326	-	1.1	-	-	-	RNP 1
TF	KK708	-	310	-	10.4	-	-	-	RNP 1
TF	KK709	-	310	-	6.4	-	-	-	RNP 1
TF	KK710	-	220	-	7.7	L	+7000	-	RNP 1
TF	KK711	-	130	-	12.2	L	+10000	-	RNP 1
TF	KK712	-	160	-	5.0	R	-	-	RNP 1
TF	IDUMI	-	160	-	17.3	-	-	-	RNP 1
TF	SALAX	-	217	-	11.4	R	-	-	RNP 1

CHANGES: REPLACE RUSBU TO MITOS ON MITOS 1E.
CHANGE BEARING & DISTANCE FOR MITOS