

STANDARD DEPARTURE CHART  
INSTRUMENT (SID) - ICAOTRANSITION ALTITUDE  
11 000 FTMIRI/MIRI (WBGR)  
RWY 02  
RNAV (GNSS)ASAKI 1A AROVU 1A BEVDO 1A  
BIPAS 1A DOXES 1A DUGEV 1A  
ESLAB 1A EXUGO 1A GODOM 1A

## DUGEV 1A DEPARTURE FOR ROUTE W446

NO.	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE/TRACK °M	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	NAV SPEC
010	CA	RWY02	-	025°	-	-	1500	-	-
020	DF	BETNA	-	-	-	L	-	-	RNAV1
030	TF	DUGEV	-	189°	29.0	L	7000	-	RNAV1

## GODOM 1A DEPARTURE FOR ROUTE G580 NORTHBOUND

NO.	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE/TRACK °M	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	NAV SPEC
010	CA	RWY02	-	025°	-	-	1500	-	-
020	DF	GODOM	-	-	-	R	7000	-	RNAV1

MINIMUM CLIMB GRADIENT (PDG) 5.0% UNTIL 7000 FT DUE TO CTR.

## EXUGO 1A DEPARTURE FOR ROUTE W450

NO.	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE/TRACK °M	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	NAV SPEC
010	CA	RWY02	-	025°	-	-	1500	-	-
020	DF	EXUGO	-	-	-	R	5000	-	RNAV1

MINIMUM CLIMB GRADIENT (PDG) 5.0% UNTIL 5000 FT DUE TO CTR.

## ESLAB 1A DEPARTURE FOR ROUTE W449

NO.	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE/TRACK °M	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	NAV SPEC
010	CA	RWY02	-	025°	-	-	1500	-	-
020	DF	ESLAB	-	-	-	R	5000	-	RNAV1

MINIMUM CLIMB GRADIENT (PDG) 5.0% UNTIL 5000 FT DUE TO CTR.

CHANGES : REMOVE THE SPEED LIMIT (KT) IN TABULAR.