

**STANDARD DEPARTURE CHART  
INSTRUMENT (SID) - ICAO**

TRANSITION ALTITUDE 11 000 FT
----------------------------------

**MIRI/MIRI (WBGR)  
RWY 20**

RNAV (GNSS)

ASAKI 1B AROVU 1B BEVDO 1B  
BIPAS 1B DOXES 1B DUGEV 1B  
ESLAB 1B EXUGO1B GODOM 1B

**TABULAR DESCRIPTION**

**ASAKI 1B DEPARTURE FOR ROUTE W442**

NO.	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE/TRACK °M	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	NAV SPEC
010	CA	RWY20	-	205°	-	-	1500	-	-
020	DF	BOLAN	-	-	-	R	-	-	RNAV1
030	TF	ASAKI	-	296°	28.4	-	7000	-	RNAV1

**AROVU 1B DEPARTURE FOR ROUTE L517**

NO.	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE/TRACK °M	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	NAV SPEC
010	CA	RWY20	-	205°	-	-	1500	-	-
020	DF	BOLAN	-	-	-	R	-	-	RNAV1
030	TF	AROVU	-	276°	26.5	L	7000	-	RNAV1

**BEVDO 1B DEPARTURE FOR ROUTE W455**

NO.	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE/TRACK °M	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	NAV SPEC
010	CA	RWY20	-	205°	-	-	1500	-	-
020	DF	BOLAN	-	-	-	R	-	-	RNAV1
030	TF	BEVDO	-	258°	25.7	L	7000	-	RNAV1

**BIPAS 1B DEPARTURE FOR ROUTE G580 WESTBOUND**

NO.	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE/TRACK °M	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	NAV SPEC
010	CA	RWY20	-	205°	-	-	1500	-	-
020	DF	ADNOX	-	-	-	-	-	-	RNAV1
030	TF	BIPAS	-	248°	26.8	R	7000	-	RNAV1

**DOXES 1B DEPARTURE FOR ROUTE W422**

NO.	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE/TRACK °M	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	NAV SPEC
010	CA	RWY20	-	205°	-	-	1500	-	-
020	DF	ADNOX	-	-	-	-	-	-	RNAV1
030	TF	DOXES	-	229°	24.9	R	7000	-	RNAV1

CHANGES : REMOVE THE SPEED LIMIT (KT) IN TABULAR.