

**STANDARD DEPARTURE CHART  
INSTRUMENT (SID) - ICAO**

TRANSITION ALTITUDE  
11,000 FT

**LABUAN/LABUAN (WBKL)  
DEPARTURES RWY 32 (RNAV 1)**

LAVED 1U  
BRUNEI 1U      IDATU 1U  
LIMBANG 1U    NOLOT 1U

**TABULAR DESCRIPTION**

**LAVED 1U**

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY-OVER	Course/ °M(°T)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT(KT)	RECOMMENDED NAVAID	NAVIGATION SPECIFICATION
VA	-	-	326°	-	-	+1500	250	-	RNAV 1
DF	LAVED	-	-	-	L	+5000	250	-	RNAV 1
TF	ESBOB	-	276°	10	R	+7000	-	-	RNAV 1

**BRUNEI 1U**

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY-OVER	Course/ °M(°T)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT(KT)	RECOMMENDED NAVAID	NAVIGATION SPECIFICATION
VA	-	-	326°	-	-	+1500	250	-	RNAV 1
DF	BRU VOR	-	-	-	L	-	-	-	RNAV 1

**LIMBANG 1U**

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY-OVER	Course/ °M(°T)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT(KT)	RECOMMENDED NAVAID	NAVIGATION SPECIFICATION
VA	-	-	326°	-	-	+1500	250	-	RNAV 1
DF	VLG VOR	-	-	-	L	-	-	-	RNAV 1

**IDATU 1U**

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY-OVER	Course/ °M(°T)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT(KT)	RECOMMENDED NAVAID	NAVIGATION SPECIFICATION
VA	-	-	326°	-	-	+1500	250	-	RNAV 1
DF	IDATU	-	-	-	R	+7000	-	-	RNAV 1
TF	LATIL	-	108°	50	L	+11000	-	-	RNAV 1

**NOLOT 1U**

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY-OVER	Course/ °M(°T)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT(KT)	RECOMMENDED NAVAID	NAVIGATION SPECIFICATION
VA	-	-	326°	-	-	+1500	250	-	RNAV 1
DF	NOLOT	-	-	-	L	+6000	-	-	RNAV 1
TF	VJN	-	052°	42	-	-	-	-	RNAV 1

**WAYPOINT LIST**

WAYPOINT IDENTIFIER	COORDINATES
NOLOT	05°27'55.70"N 115°28'53.71"N
IDATU	05°09'10.72"N 115°39'10.11"N
ESBOB	05°21'23.69"N 114°40'39.53"N
LAVED	05°20'25.08"N 114°50'36.08"N
BRU	04°52'28.52"N 114°53'07.77"E
VLG	04°47'50.20"N 115°00'08.40"N
VJN	05°53'57.30"N 116°02'02.30"N
LATIL	04°53'39.84"N 116°26'48.84"N

CHANGES : UPDATING THE CHART FORMAT.