

**STANDARD ARRIVAL CHART  
INSTRUMENT (STAR) - ICAO**

TRANSITION ALTITUDE  
11,000 FT

**LABUAN/LABUAN (WBKL)  
ARRIVAL RWY 32 (RNAV 1)**

LAVED 1T  
BRUNEI 1T  
LIMBANG 1T  
IDATU 1T  
NOLOT 1T

**TABULAR DESCRIPTION**

**LAVED 1T**

SERIAL NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY-OVER	COURSE/°M(°T)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT(KT)	RECOMMENDED NAVAID	TCH/VPA	NAVIGATION SPECIFICATION
010	IF	ESBOB	-	-	-	-	+FL 130	-	-	-	RNAV 1
020	TF	LAVED	-	096°(95.6°)	10.0	-	+11000	-	-	-	RNAV 1
030	TF	UKIBA	-	098°(97.9°)	11.60	-	+9000	-	-	-	RNAV 1
040	TF	KAPLA	-	127.0°(127.1°)	9.50	R	+7000	250	-	-	RNAV 1
050	TF	GUSRI	-	135.0°(134.6°)	12.70	R	+3000	250	-	-	RNAV 1
060	TF	IDRIP	-	036°(35.6°)	5.0	L	+2000	220	-	-	RNAV 1

**BRUNEI 1T**

SERIAL NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY-OVER	COURSE/°M(°T)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT(KT)	RECOMMENDED NAVAID	TCH/VPA	NAVIGATION SPECIFICATION
010	IF	BRU	-	-	-	-	-	-	-	-	RNAV 1
020	TF	GUSRI	-	066°(65.6°)	28.1	-	+3000	250	-	-	RNAV 1
030	TF	IDRIP	-	036°(35.6°)	5.0	L	+2000	220	-	-	RNAV 1

**LIMBANG 1T**

SERIAL NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY-OVER	COURSE/°M(°T)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT(KT)	RECOMMENDED NAVAID	TCH/VPA	NAVIGATION SPECIFICATION
010	IF	VLG	-	-	-	-	-	-	-	-	RNAV 1
020	TF	GUSRI	-	049°(48.9°)	24.7	-	+3000	250	-	-	RNAV 1
030	TF	IDRIP	-	036°(5.6°)	5.0	R	+2000	220	-	-	RNAV 1

**IDATU 1T**

SERIAL NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY-OVER	COURSE/°M(°T)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT(KT)	RECOMMENDED NAVAID	TCH/VPA	NAVIGATION SPECIFICATION
010	IF	LATIL	-	-	-	-	+9000	-	-	-	RNAV 1
020	TF	IDATU	-	288°(288.0°)	50.0	-	+7000	-	-	-	RNAV 1
030	TF	TAVAD	-	272°(271.3°)	12.6	L	+3000	250	-	-	RNAV 1
040	TF	IDRIP	-	256°(255.6°)	5.0	L	+2000	220	-	-	RNAV 1

**NOLOT 1T**

SERIAL NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY-OVER	COURSE/°M(°T)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT(KT)	RECOMMENDED NAVAID	TCH/VPA	NAVIGATION SPECIFICATION
010	IF	VJN	-	-	-	-	-	-	-	-	RNAV 1
020	TF	NOLOT	-	232°(231.9°)	42.0	-	+9000	-	-	-	RNAV 1
030	TF	IGNOP	-	232°(231.9°)	9.9	-	+7000	250	-	-	RNAV 1
040	TF	TAVAD	-	156°(156.1°)	13.4	L	+3000	250	-	-	RNAV 1
050	TF	IDRIP	-	256°(255.6°)	5.0	R	+2000	220	-	-	RNAV 1

**HOLDINGS**

FIX ID	PATH TERMINATOR	FLY-OVER	COURSE/°M(°T)	TIME	TURN DIRECTION	MNM ALT (FT)	SPEED LIMIT(KT)	RECOMMENDED NAVAID	FLY-OVER	NAVIGATION SPECIFICATION
NOLOT	HM	Y	232°	1 MIN	R	5500	230	-	-	RNAV 1
KAPLA	HM	Y	135°	1 MIN	R	5500	220	-	-	RNAV 1

CHANGES : UPDATING THE CHART FORMAT.