

KOTA KINABALU / KOTA KINABALU
(WBKK)
RWY 20
DEPARTURES (RIGHT TURN)
(RNAV 1)

STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO

TRANSITION ALTITUDE
11,000 FT

TABULAR DESCRIPTION

ROUTE DESIGNATOR	SERIAL NUMBER	PATH DESCRIPTOR	WP IDENTIFIER	FLY OVER	COURSE/ °(T)	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED (KT) IAS MAX	RECOMMENDED NAVAID	NAVIGATION SPECIFICATION
ENBAX 1G	010	CF	DAGIR	Y	202°	-	3.2	-	-	205	VJN VOR/DME	RNAV 1
	020	DF	POLEB	-	-	-	-	R	+4000	-	-	RNAV 1
	030	TF	ENBAX	-	016°	-	47.8	R	-	-	-	-

VETAG 1G	010	CF	DAGIR	Y	202°	-	3.2	-	-	205	VJN DVOR/DME	RNAV 1
	020	DF	POLEB	-	-	-	-	R	+4000	-	-	RNAV 1
	030	TF	PEDSI	-	046°	-	8	R	+6500	-	-	RNAV 1
	040	TF	EMTEN	-	046°	-	24	-	+9000	-	-	RNAV 1
	050	TF	VETAG	-	046°	-	21.4	-	-	-	-	RNAV 1

KABDU 1G	010	CF	DAGIR	Y	202°	-	3.2	-	-	205	VJN DVOR/DME	RNAV 1
	020	DF	POLEB	-	-	-	-	R	+4000	-	-	RNAV 1
	030	TF	PEDSI	-	046°	-	8	R	+6500	-	-	RNAV 1
	040	TF	EMTEN	-	046°	-	24	-	+9000	-	-	RNAV 1
	050	TF	KABDU	-	054°	-	22	R	-	-	-	RNAV 1

ANLOD 2L	010	CF	DAGIR	Y	202°	-	3.2	-	-	205	VJN DVOR/DME	RNAV 1
	020	DF	POLEB	-	-	-	-	R	+4000	-	-	RNAV 1
	030	TF	PEDSI	-	046°	-	8	R	+6500	-	-	RNAV 1
	040	TF	SATKO	-	119°	-	15.6	R	+9000	-	-	RNAV 1
	050	TF	ANLOD	-	093°	-	30	L	+FL170	-	-	RNAV 1

TUSVU 1L	010	CF	DAGIR	Y	202°	-	3.2	-	-	205	VJN DVOR/DME	RNAV 1
	020	DF	POLEB	-	-	-	-	R	+4000	-	-	RNAV 1
	030	TF	PEDSI	-	046°	-	8	R	+6500	-	-	RNAV 1
	040	TF	SATKO	-	119°	-	15.6	R	+9000	-	-	RNAV 1
	050	TF	TUSVU	-	119°	-	31.6	-	+11000	-	-	RNAV 1

MAKSU 2L	010	CF	DAGIR	Y	202°	-	3.2	-	-	205	VJN DVOR/DME	RNAV 1
	020	DF	POLEB	-	-	-	-	R	+4000	-	-	RNAV 1
	030	TF	PEDSI	-	046°	-	8	R	+6500	-	-	RNAV 1
	040	TF	SATKO	-	119°	-	15.6	R	+9000	-	-	RNAV 1
	050	TF	MAKSU	-	140°	-	33.8	R	+11000	-	-	RNAV 1

NOTE : INITIAL CLIMB AT MNM GR 5% ON RWY HDG, TURN RIGHT AT DAGIR, CONTINUE AT 5% MNM PDG UNTIL 6500FT. RESUME NORMAL CLIMB THEREAFTER.

ROUTE DESIGNATOR	SERIAL NUMBER	PATH DESCRIPTOR	WP IDENTIFIER	FLY OVER	COURSE/ °(T)	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED (KT) IAS MAX	RECOMMENDED NAVAID	NAVIGATION SPECIFICATION
PIMEP 2G	010	CF	DAGIR	Y	202°	-	3.2	-	-	205	VJN VOR/DME	RNAV 1
	020	DF	UGUKI	-	-	-	17	R	-	-	-	RNAV 1
	030	TF	PIMEP	-	208°	-	21.8	L	-	-	-	RNAV 1

OREKO 1G	010	CF	DAGIR	Y	202°	-	3.2	-	-	205	VJN VOR/DME	RNAV 1
	020	DF	UGUKI	-	-	-	17	R	-	-	-	RNAV 1
	030	TF	OREKO	-	217°	-	21.3	L	-	-	-	RNAV 1

DULIM 2G	010	CF	DAGIR	Y	202°	-	3.2	-	-	205	VJN VOR/DME	RNAV 1
	020	DF	UGUKI	-	-	-	17	R	-	-	-	RNAV 1
	030	TF	DULIM	-	227°	-	21.1	-	-	-	-	RNAV 1

CHANGES : UPDATING THE CHART FORMAT