

**STANDARD DEPARTURE CHART  
INSTRUMENT (SID) - ICAO**

TRANSITION ALTITUDE 11000 FT
---------------------------------

**SEPANG/KL INTERNATIONAL  
AIRPORT (WMKK)  
RNP 1 (GNSS) RWY 14R**

PUGER 2B    BIKDU 2B    SALAX 2B  
IBUKU 2B    PIBOS 2B    MITOS 2B  
ATIMU 2B    KIMAT 2B    RUSBU 2B

**KIMAT TWO BRAVO DEPARTURE (KIMAT 2B)**

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK734	-	146	-	7.2	-	-	-	RNP 1
TF	KK733	-	056	-	9.0	L	+3000	-	RNP 1
TF	KIMAT	-	043	-	38.5	-	-	-	RNP 1

**RUSBU TWO BRAVO DEPARTURE (RUSBU 2B)**

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK734	-	146	-	7.2	-	-	-	RNP 1
TF	RUSBU	-	129	-	55.3	-	-	-	RNP 1

**MITOS TWO BRAVO DEPARTURE (MITOS 2B)**

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK734	-	146	-	7.2	-	-	-	RNP 1
TF	MITOS	-	153	-	41.8	R	-	-	RNP 1

**SALAX TWO BRAVO DEPARTURE (SALAX 2B)**

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK734	-	146	-	7.2	-	-	-	RNP 1
TF	KK731	-	236	-	9.0	R	-	-	RNP 1
TF	SALAX	-	199	-	19.7	L	-	-	RNP 1

CHANGES : NEW CHART.