

**STANDARD ARRIVAL CHART
INSTRUMENT (STAR) - ICAO**

**SUBANG/SULTAN ABDUL
AZIZ SHAH (WMSA)
RNAV RWY 15**

TRANSITION ALTITUDE
11000 FT

PUGER 2M NIREN 2M KAKAK 2M
PULIP 2M SAROX 2M GUPTA 2M
SALAX 2M

TABULAR DESCRIPTION

PUGER TWO MIKE ARRIVAL (PUGER 2M)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (M)	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	PUGER	-	-	-	-	-	-	-	RNAV1
TF	BORDU	-	095°	-	36.3	-	-	-	RNAV1
TF	SA601	-	060°	-	37.3	L	-	-	RNAV1
TF	SA602	-	150°	-	5.0	R	-	-	RNAV1
TF	SA603	-	150°	-	5.0	-	+ 8000	-	RNAV1
TF	SA604	-	150°	-	5.0	-	-	-	RNAV1
TF	SA605	-	150°	-	4.5	-	-	- 230	RNAV1
TF	SA606	-	240°	-	5.0	R	-	-	RNAV1
TF	SA607	-	330°	-	4.5	R	-	-	RNAV1
TF	SA608	-	330°	-	5.0	-	-	- 210	RNAV1
TF	SA609	-	330°	-	5.0	-	-	-	RNAV1
TF	SA610	-	240°	-	5.0	L	-	-	RNAV1
TF	SA611	-	150°	-	5.0	L	+ 4000	-	RNAV1

NIREN TWO MIKE ARRIVAL (NIREN 2M)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (M)	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	NIREN	-	-	-	-	-	-	-	RNAV1
TF	BORDU	-	114°	-	22.7	-	-	-	RNAV1
TF	SA601	-	060°	-	37.3	L	-	-	RNAV1
TF	SA602	-	150°	-	5.0	R	-	-	RNAV1
TF	SA603	-	150°	-	5.0	-	+ 8000	-	RNAV1
TF	SA604	-	150°	-	5.0	-	-	-	RNAV1
TF	SA605	-	150°	-	4.5	-	-	- 230	RNAV1
TF	SA606	-	240°	-	5.0	R	-	-	RNAV1
TF	SA607	-	330°	-	4.5	R	-	-	RNAV1
TF	SA608	-	330°	-	5.0	-	-	- 210	RNAV1
TF	SA609	-	330°	-	5.0	-	-	-	RNAV1
TF	SA610	-	240°	-	5.0	L	-	-	RNAV1
TF	SA611	-	150°	-	5.0	L	+ 4000	-	RNAV1

NEW TABULAR