

**STANDARD DEPARTURE CHART  
INSTRUMENT (SID) - ICAO**

TRANSITION ALTITUDE  
11000FT

**SUBANG/SULTAN ABDUL  
AZIZ SHAH (WMSA)  
RNAV RWY 15**  
BIKDU 3L PIBOS 3L RUSBU 3L  
MITOS 3L SALAX 3L PUGER 3L  
IBUKU 3L ATIMU 3L

**TABULAR DESCRIPTION**

**SALAX THREE LIMA DEPARTURE (SALAX 3L)**

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (M)	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	SA641	-	150°	-	5.0	-	-	-	RNAV 1
TF	SA644	-	060°	-	5.5	L	+2500	-210	RNAV 1
TF	SA645	-	060°	-	4.5	-	-	-	RNAV 1
TF	SA636	-	124°	-	13.9	R	-	-	RNAV 1
TF	SA638	-	150°	-	22.4	R	-	-	RNAV 1
TF	SA639	-	150°	-	8.2	-	-	-	RNAV 1
TF	DUMOK	-	217°	-	19.4	R	-	-	RNAV 1
TF	SALAX	-	258°	-	27.0	R	-	-	RNAV 1

MINIMUM CLIMB GRADIENT (PDG) 5.5% UNTIL SA644 DUE TO OBSTACLE.

**PUGER THREE LIMA DEPARTURE (PUGER 3L)**

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (M)	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	SA641	-	150°	-	5.0	-	-	-	RNAV 1
TF	SA642	-	240°	-	8.0	R	@2500	-210	RNAV 1
TF	SA643	-	274°	-	12.0	R	-	-	RNAV 1
TF	SADGI	-	274°	-	10.6	-	-	-	RNAV 1
TF	RUPDO	-	331°	-	15.9	R	-	-	RNAV 1
TF	PUGER	-	284°	-	42.4	L	-	-	RNAV 1

MINIMUM CLIMB GRADIENT (PDG) 5.5% UNTIL 2500FT DUE TO OBSTACLE.

**IBUKU THREE LIMA DEPARTURE (IBUKU 3L)**

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (M)	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	SA641	-	150°	-	5.0	-	-	-	RNAV 1
TF	SA642	-	240°	-	8.0	R	@2500	-210	RNAV 1
TF	SA643	-	274°	-	12.0	R	-	-	RNAV 1
TF	SADGI	-	274°	-	10.6	-	-	-	RNAV 1
TF	RUPDO	-	331°	-	15.9	R	-	-	RNAV 1
TF	IBUKU	-	331°	-	24.5	-	-	-	RNAV 1

MINIMUM CLIMB GRADIENT (PDG) 5.5% UNTIL 2500FT DUE TO OBSTACLE.

**ATIMU THREE LIMA DEPARTURE (ATIMU 3L)**

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (M)	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	SA641	-	150°	-	5.0	-	-	-	RNAV 1
TF	SA642	-	240°	-	8.0	R	@2500	-210	RNAV 1
TF	SA643	-	274°	-	12.0	R	-	-	RNAV 1
TF	SADGI	-	274°	-	10.6	-	-	-	RNAV 1
TF	RUPDO	-	331°	-	15.9	R	-	-	RNAV 1
TF	ATIMU	-	360°	-	26.1	R	-	-	RNAV 1

MINIMUM CLIMB GRADIENT (PDG) 5.5% UNTIL 2500FT DUE TO OBSTACLE.

NEW TABULAR