

**STANDARD ARRIVAL CHART
INSTRUMENT (STAR) - ICAO**

**SUBANG/SULTAN ABDUL
AZIZ SHAH (WMSA)
RNAV RWY 15**

TRANSITION ALTITUDE
11000 FT

PUGER 2M NIREN 2M KAKAK 2M
PULIP 2M SAROX 2M GUPTA 2M
SALAX 2M

SAROX TWO MIKE ARRIVAL (SAROX 2M)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (M)	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	SAROX	-	-	-	-	-	-	-	RNAV1
TF	SA624	-	243°	-	32.4	-	-	-	RNAV1
TF	SA622	-	279	-	20.0	R	-	-	RNAV1
TF	SA621	-	314	-	10.3	R	-	-	RNAV1
TF	SA620	-	345°	-	29.1	R	+ 7000	- 230	RNAV1
TF	SA606	-	330°	-	10.0	L	-	-	RNAV1
TF	SA607	-	330°	-	4.5	-	-	-	RNAV1
TF	SA608	-	330°	-	5.0	-	-	- 210	RNAV1
TF	SA609	-	330°	-	5.0	-	-	-	RNAV1
TF	SA610	-	240°	-	5.0	L	-	-	RNAV1
TF	SA611	-	150°	-	5.0	L	+ 4000	-	RNAV1

GUPTA TWO MIKE ARRIVAL (GUPTA 2M)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (M)	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	GUPTA	-	-	-	-	-	-	-	RNAV1
TF	SA623	-	292°	-	36.1	-	-	-	RNAV1
TF	SA622	-	314°	-	18.5	R	-	-	RNAV1
TF	SA621	-	314°	-	10.3	-	-	-	RNAV1
TF	SA620	-	345°	-	29.1	R	+ 7000	- 230	RNAV1
TF	SA606	-	330°	-	10.0	L	-	-	RNAV1
TF	SA607	-	330°	-	4.5	-	-	-	RNAV1
TF	SA608	-	330°	-	5.0	-	-	- 210	RNAV1
TF	SA609	-	330°	-	5.0	-	-	-	RNAV1
TF	SA610	-	240°	-	5.0	L	-	-	RNAV1
TF	SA611	-	150°	-	5.0	L	+ 4000	-	RNAV1

NEW TABULAR