

STANDARD ARRIVAL CHART
INSTRUMENT (STAR) - ICAO

TRANSITION ALTITUDE
11000 FT

SIBU/SIBU (WBGS)
RNAV (GNSS) RWY 13
NOLUS 1E REDUK 1E LENTU 1E
ELNAL 1E BIPIB 1E ANKUP 1E
PILAX 1E

TABULAR DESCRIPTION

NOLUS ONE ECHO ARRIVAL (NOLUS 1E)

PATH TERMINATOR	WAYPOINT	FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	NOLUS	-	-	-	-	+5000	-	-
TF	LELIP (IAF)	-	228	11.1	-	+3000	-	RNAV 1
TF	NOKAL (IF)	-	220	5.0	-	+2500	-	RNP APCH

REDUK ONE ECHO ARRIVAL (REDUK 1E)

PATH TERMINATOR	WAYPOINT	FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	REDUK	-	-	-	-	+7000	-	-
TF	TAMIG	-	229	13.1	-	+5000	-	RNAV 1
TF	LELIP (IAF)	-	256	30.4	R	+3000	-	RNAV 1
TF	NOKAL (IF)	-	220	5.0	L	+2500	-	RNP APCH

LENTU ONE ECHO ARRIVAL (LENTU 1E)

PATH TERMINATOR	WAYPOINT	FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	LENTU	-	-	-	-	+7000	-	-
TF	APPAD	-	248	10.0	-	+5000	-	RNAV 1
TF	LELIP (IAF)	-	272	35.0	R	+3000	-	RNAV 1
TF	NOKAL (IF)	-	220	5.0	L	+2500	-	RNP APCH

ELNAL ONE ECHO ARRIVAL (ELNAL 1E)

PATH TERMINATOR	WAYPOINT	FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	ELNAL	-	-	-	-	+7000	-	-
TF	TULMA	-	045	10.0	-	+5000	-	RNAV 1
TF	RINRA (IAF)	-	016	27.2	L	+3000	-	RNAV 1
TF	NOKAL (IF)	-	040	5.0	R	+2500	-	RNP APCH

BIPIB ONE ECHO ARRIVAL (BIPIB 1E)

PATH TERMINATOR	WAYPOINT	FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	BIPIB	-	-	-	-	+7000	-	-
TF	MEGOX	-	067	10.0	-	+5000	-	RNAV 1
TF	RINRA (IAF)	-	038	22.2	L	+3000	-	RNAV 1
TF	NOKAL (IF)	-	040	5.0	-	+2500	-	RNP APCH

CHANGES: AT ELNAL ONE ECHO ARRIVAL (ELNAL 1E) TABULAR AMEND
GS363 TO ELNAL