

**STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO**

TRANSITION ALTITUDE 11000 FT

**SEPANG/KL INTERNATIONAL
AIRPORT (WMKK)
RNAV (GNSS) RWY 32L**

PUGER 1E	BIKDU 1E	SALAX 1E
IBUKU 1E	PIBOS 1E	MITOS 1E
ATIMU 1E	KIMAT 1E	RUSBU 1E

IBUKU ONE ECHO DEPARTURE (IBUKU 1E)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK707	Y	326	-	1.1		-	-	RNP 1
TF	KK708	-	310	-	10.4	-	-	-	RNP 1
TF	GUTIK	-	324	-	19.8	R	-	-	RNP 1
TF	IBUKU	-	308	-	44.2	L	-	-	RNP 1

PUGER ONE ECHO DEPARTURE (PUGER 1E)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK707	Y	326	-	1.1		-	-	RNP 1
TF	KK708	-	310	-	10.4	-	-	-	RNP 1
TF	GUTIK	-	324	-	19.8	R	-	-	RNP 1
TF	RUPDO	-	284	-	23.6	L	-	-	RNP 1
TF	PUGER	-	284	-	42.4	-	-	-	RNP 1

ATIMU ONE ECHO DEPARTURE (ATIMU 1E)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK707	Y	326	-	1.1		-	-	RNP 1
TF	KK708	-	310	-	10.4	-	-	-	RNP 1
TF	GUTIK	-	324	-	19.8	R	-	-	RNP 1
TF	ATIMU	-	324	-	39.1	-	-	-	RNP 1

BIKDU ONE ECHO DEPARTURE (BIKDU 1E)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK707	Y	326	-	1.1		-	-	RNP 1
TF	KK708	-	310	-	10.4	-	-	-	RNP 1
TF	GUTIK	-	324	-	19.8	R	-	-	RNP 1
TF	BIKDU	-	005	-	42.1	R	-	-	RNP 1

CHANGES: CHANGE DISTANCE FOR PUGER.