

STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAOTRANSITION ALTITUDE
11000 FTKOTA BHARU/
SULTAN ISMAIL PETRA (WMKC)
RNAV (GNSS) RWY 28OPOMO 1B GUGIT 1B
DUBMU 1B RUPOS 1B

TABULAR DESCRIPTION

GUGIT ONE BRAVO DEPARTURE (GUGIT 1B)

SERIAL NO.	PATH TERMINATOR	WAYPOINT NAME	FLY OVER	COURSE °M	DIST (NM)	TURN DIR.	LEVEL CONSTRAINT (FT)	SPEED LIMIT (KT)	PDG (%)	NAVIGATION SPECIFICATION
1	VA	-	-	280°	-	-	+1000	-	5.2	RNAV 1
2	DF	BIXOR	-	-	-	L	+5000	-	5.2	RNAV 1
3	TF	GUGIT	-	142°	34.6	L	+11000	-	3.3	RNAV 1

RUPOS ONE BRAVO DEPARTURE (RUPOS 1B)

SERIAL NO.	PATH TERMINATOR	WAYPOINT NAME	FLY OVER	COURSE °M	DIST (NM)	TURN DIR.	LEVEL CONSTRAINT (FT)	SPEED LIMIT (KT)	PDG (%)	NAVIGATION SPECIFICATION
1	VA	-	-	280°	-	-	+1000	-	5.2	RNAV 1
2	DF	BIXOR	-	-	-	L	+5000	-	5.2	RNAV 1
3	TF	RUPOS	-	180°	27.6	-	+11000	-	3.3	RNAV 1

OPOMO ONE BRAVO DEPARTURE (OPOMO 1B)

SERIAL NO.	PATH TERMINATOR	WAYPOINT NAME	FLY OVER	COURSE °M	DIST (NM)	TURN DIR.	LEVEL CONSTRAINT (FT)	SPEED LIMIT (KT)	PDG (%)	NAVIGATION SPECIFICATION
1	VA	-	-	280°	-	-	+1000	-	5.2	RNAV 1
2	DF	NISED	-	-	-	L	+5000	-	5.2	RNAV 1
3	TF	OPOMO	-	202°	27.1	-	+11000	-	3.6	RNAV 1

DUBMU ONE BRAVO DEPARTURE (DUBMU 1B)

SERIAL NO.	PATH TERMINATOR	WAYPOINT NAME	FLY OVER	COURSE °M	DIST (NM)	TURN DIR.	LEVEL CONSTRAINT (FT)	SPEED LIMIT (KT)	PDG (%)	NAVIGATION SPECIFICATION
1	VA	-	-	280°	-	-	+1000	-	5.2	RNAV 1
2	DF	BIXOR	-	-	-	L	+5000	-	5.2	RNAV 1
3	TF	DUBMU	-	165°	31.1	-	+11000	-	3.3	RNAV 1

CHANGES: CHANGE BIXOR TURN DIRECTION,
CHANGE DUBMU COURSE TO 165°.