

**STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO**TRANSITION ALTITUDE
11000FT**SANDAKAN/SANDAKAN (WBKS)****RNAV RWY 08**KUDAT 1B
AKMAR 1BBELDA 1B
ANKOB 1B
LAHAD 1B**TABULAR DESCRIPTION****KUDAT ONE BRAVO DEPARTURE (KUDAT 1B)**

SEQ	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KIAS)	NAVIGATION SPECIFICATION
010	CA	-	-	081°	-	-	+1400	-	RNAV 1
020	DF	RUNDU	-	-	-	L	+6000	-	RNAV 1

BELDA ONE BRAVO DEPARTURE (BELDA 1B)

SEQ	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KIAS)	NAVIGATION SPECIFICATION
010	CA	-	-	081°	-	-	+1400	-	RNAV 1
020	DF	IDURI	-	-	-	L	+6000	-	RNAV 1
030	TF	UPSOP	-	280°	13.8	-	+9000	-	RNAV 1
040	TF	BELDA	-	294°	13.0	R	-	-	RNAV 1

AKMAR ONE BRAVO DEPARTURE (AKMAR 1B)

SEQ	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KIAS)	NAVIGATION SPECIFICATION
010	CA	-	-	081°	-	-	+1400	-	RNAV 1
020	DF	IDURI	-	-	-	L	+6000	-	RNAV 1
030	TF	GUSMO	-	245°	17.4	L	+8000	-	RNAV 1
040	TF	AKMAR	-	271°	13.0	R	-	-	RNAV 1

ANKOB ONE BRAVO DEPARTURE (ANKOB 1B)

SEQ	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KIAS)	NAVIGATION SPECIFICATION
010	CA	-	-	081°	-	-	+1400	-	RNAV 1
020	DF	OMBUN	-	-	-	R	+4500	-	RNAV 1
030	TF	SUKIL	-	233°	8.1	-	-	-	RNAV 1
040	TF	UGPEM	-	290°	21.6	R	+8000	-	RNAV 1
050	TF	ANKOB	-	254°	13.2	L	-	-	RNAV 1