

**STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO**

TRANSITION ALTITUDE 11000 FT

**SEPANG/KL INTERNATIONAL
AIRPORT (WMKK)
RNP 1 (GNSS) RWY 14R**

PUGER 2B	BIKDU 2B	SALAX 2B
IBUKU 2B	PIBOS 2B	MITOS 2B
ATIMU 2B	KIMAT 2B	RUSBU 2B

KIMAT TWO BRAVO DEPARTURE (KIMAT 2B)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK734	-	146	-	7.2	-	-	-	RNP 1
TF	KK733	-	056	-	9.0	L	+3000	-	RNP 1
TF	KIMAT	-	043	-	38.5	-	-	-	RNP 1

RUSBU TWO BRAVO DEPARTURE (RUSBU 2B)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK734	-	146	-	7.2	-	-	-	RNP 1
TF	RUSBU	-	129	-	55.3	-	-	-	RNP 1

MITOS TWO BRAVO DEPARTURE (MITOS 2B)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK734	-	146	-	7.2	-	-	-	RNP 1
TF	MITOS	-	153	-	41.8	R	-	-	RNP 1

SALAX TWO BRAVO DEPARTURE (SALAX 2B)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK734	-	146	-	7.2	-	-	-	RNP 1
TF	KK731	-	236	-	9.0	R	-	-	RNP 1
TF	SALAX	-	199	-	19.7	L	-	-	RNP 1

CHANGES : NEW CHART.