

**STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO**

TRANSITION ALTITUDE
11000 FT

**SEPANG/KL INTERNATIONAL
AIRPORT (WMKK)
RNP 1 (GNSS) RWY 33**

PUGER 2F BIKDU 2F SALAX 2F
IBUKU 2F PIBOS 2F MITOS 2F
ATIMU 2F KIMAT 2F RUSBU 2F

TABULAR DESCRIPTION

PUGER TWO FOXTROT DEPARTURE (PUGER 2F)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK743	-	326	-	7.5	-	-	-	RNP 1
TF	RUPDO	-	302	-	44.3	L	-	-	RNP 1
TF	PUGER	-	284	-	42.3	L	-	-	RNP 1

IBUKU TWO FOXTROT DEPARTURE (IBUKU 2F)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK743	-	326	-	7.5	-	-	-	RNP 1
TF	IBUKU	-	312	-	66.9	-	-	-	RNP 1

ATIMU TWO FOXTROT DEPARTURE (ATIMU 2F)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK743	-	326	-	7.5	-	-	-	RNP 1
TF	ATIMU	-	323	-	62.2	-	-	-	RNP 1

BIKDU TWO FOXTROT DEPARTURE (BIKDU 2F)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK743	-	326	-	7.5	-	-	-	RNP 1
TF	KK741	-	001	-	42.3	R	-	-	RNP 1
TF	BIKDU	-	325	-	21.3	L	-	-	RNP 1

PIBOS TWO FOXTROT DEPARTURE (PIBOS 2F)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK743	-	326	-	7.5	-	-	-	RNP 1
TF	KK740	-	056	-	10.2	R	+3000	-	RNP 1
TF	PIBOS	-	037	-	30.2	L	-	-	RNP 1

KIMAT TWO FOXTROT DEPARTURE (KIMAT 2F)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK743	-	326	-	7.5	-	-	-	RNP 1
TF	KK740	-	056	-	10.2	R	+3000	-	RNP 1
TF	KIMAT	-	070	-	38.6	-	-	-	RNP 1

CHANGES : NEW CHART.