


**INSTRUMENT
APPROACH
CHART - ICAO**

AERODROME ELEV 88 FT
HEIGHTS RELATED TO
THR RWY 25 - ELEV 42 FT
ILS REF DATUM 54 FT

TWR	118.1 (P)	SMC	121.9
	121.7 (S)	ATIS	128.4
APP	120.2 (P)	FIS	134.75
	123.85 (S)		
ACC	134.5 (P)		
	125.35 (S)		

**KUCHING/KUCHING (WBGG)
RWY 25**

ILS Z/ LOC Z
(FROM STAR)




DIST BY DME (NM)	7.1	6.1	5.1	4.1	3.1	2.1	1.1
ALT 3° APCH PATH (FT)	2300 (2258)	1982 (1940)	1664 (1622)	1346 (1304)	1028 (986)	710 (668)	443 (401)

TRANSITION ALT 11,000

MISSED APPROACH

CLIMB ON 248° TO 1000 FT OR ABOVE
TURN RIGHT AFTER VKG, BUT NOT LATER THAN 1.5 DME
INTERCEPT RDL 003 TO DOTUG HOLD AT 4500 FT
OR AS DIRECTED BY ATC



OCA (H) FT		A	B	C	D
STRAIGHT-IN APPROACH	CAT. 1	243 (201)	243 (201)	245 (203)	256 (214)
	GP INOP.	443 (401) / 1.1 IKG			
CIRCLING		750 (662)	750 (662)	1200 (1112)	1200 (1112)

GROUND SPEED(KT)		70	90	120	150	180	210
FAP - MAPT = 6.0NM		MIN : SEC	5:08	4:00	3:00	2:24	2:00
RATE OF DESCENT (3°)		FT./ MIN	354	455	607	759	911
						1063	

CHANGES : CHANGE AERODROME ELEVATION TO 88 FT AND THR RWY 25 ELEVATION TO 42 FT.