

STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO

TRANSITION ALTITUDE
11000FT

MALACCA/MALACCA (WMKM)
RNAV (GNSS) RWY 21

RUSBU 1R OGAKO 1R
DOSIK 1R SAPAT 3R
IRMB 3R

TABULAR DESCRIPTION

RUSBU ONE ROMEO DEPARTURE (RUSBU 1R)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CA	-	-	210	-	-	+2500	-	-
DF	LAVIG	-	-	-	L	+5000	-	RNAV 1
TF	RUSBU	-	090	15.3	L	+6000	-	RNAV 1

MINIMUM CLIMB GRADIENT (PDG) 4.5% UNTIL PASSING 5000 FT DUE TO OBSTACLE & RESTRICTED AREA UPPER LIMIT.

OGAKO ONE ROMEO DEPARTURE (OGAKO 1R)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CA	-	-	210	-	-	+2500	-	-
DF	LAVIG	-	-	-	L	+5000	-	RNAV 1
TF	OGAKO	-	103	11.0	L	+6000	-	RNAV 1

MINIMUM CLIMB GRADIENT (PDG) 4.5% UNTIL PASSING 5000 FT DUE TO OBSTACLE & RESTRICTED AREA UPPER LIMIT.

DOSIK ONE ROMEO DEPARTURE (DOSIK 1R)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CA	-	-	210	-	-	+2500	-	-
DF	DOSIK	-	-	-	-	+7000	-	RNAV 1

MINIMUM CLIMB GRADIENT (PDG) 4.5% UNTIL PASSING 2500 FT DUE TO OBSTACLE.

SAPAT THREE ROMEO DEPARTURE (SAPAT 3R)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CA	-	-	210	-	-	+1500	-	-
DF	KM501	-	-	-	R	+2500	-	RNAV 1
TF	KM503	-	008	12.9	-	+5000	-	RNAV 1
TF	SAPAT	-	324	9.0	L	+7000	-	RNAV 1

MINIMUM CLIMB GRADIENT (PDG) 4.5% UNTIL PASSING 1500 FT DUE TO OBSTACLE.

NEW TABULAR