

**STANDARD DEPARTURE CHART  
INSTRUMENT (SID) - ICAO**

**TRANSITION ALTITUDE**  
11000 ft

**KUANTAN/SULTAN AHMAD  
SHAH (WMKD)**  
**RNAV (GNSS) RWY 36**  
OSTIN 1C VPK 1C  
MEVOK 1C OSIKU 1C  
DAGAG 1C

**TABULAR DESCRIPTION**

**OSTIN ONE CHARLIE DEPARTURE (OSTIN 1C)**

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KD251	-	003	9.6	-	+2500	-	-
TF	OSTIN	-	023	20.3	R	+4000	-	RNAV 1

MINIMUM CLIMB GRADIENT (PDG) OF 4.5% IS REQUIRED UNTIL KD251.

**VPK ONE CHARLIE DEPARTURE (VPK 1C)**

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KD251	-	003	9.6	-	+2500	-	-
TF	KD252	-	093	8.0	R	-	-	RNAV 1
TF	KD253	-	159	18.7	R	-	-	RNAV 1
TF	VPK	-	189	15.8	R	+8000	-	RNAV 1

MINIMUM CLIMB GRADIENT (PDG) OF 4.5% IS REQUIRED UNTIL KD251.

**MEVOK ONE CHARLIE DEPARTURE (MEVOK 1C)**

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KD251	-	003	9.6	-	+2500	-	-
TF	KD254	-	273	8.0	L	-	-	RNAV 1
TF	KD255	-	242	9.5	L	-	-	RNAV 1
TF	MEVOK	-	200	25.3	L	+7000	-	RNAV 1

MINIMUM CLIMB GRADIENT (PDG) OF 4.5% IS REQUIRED UNTIL KD251.

**OSIKU ONE CHARLIE DEPARTURE (OSIKU 1C)**

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KD251	-	003	9.6	-	+2500	-	-
TF	KD254	-	273	8.0	L	-	-	RNAV 1
TF	KD255	-	242	9.5	L	-	-	RNAV 1
TF	OSIKU	-	242	16.2	-	+9500	-	RNAV 1

MINIMUM CLIMB GRADIENT (PDG) OF 4.5% IS REQUIRED UNTIL KD251.

NEW TABULAR