

STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO

TRANSITION ALTITUDE
11, 000 FT

LABUAN/LABUAN (WBKL)
DEPARTURES RWY 32 (RNAV 1)

LAVED 1U
BRUNEI 1U IDATU 1U
LIMBANG 1U NOLOT 1U

TABULAR DESCRIPTION
LAVED 1U

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY-OVER	Course/°M(°T)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT(KT)	RECOMMENDED NAVAID	NAVIGATION SPECIFICATION
VA	-	-	326°	-	-	+1500	250	-	RNAV 1
DF	LAVED	-	-	-	L	+5000	250	-	RNAV 1
TF	ESBOB	-	276°	10	R	+7000	-	-	RNAV 1

BRUNEI 1U

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY-OVER	Course/°M(°T)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT(KT)	RECOMMENDED NAVAID	NAVIGATION SPECIFICATION
VA	-	-	326°	-	-	+1500	250	-	RNAV 1
DF	BRU VOR	-	-	-	L	-	-	-	RNAV 1

LIMBANG 1U

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY-OVER	Course/°M(°T)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT(KT)	RECOMMENDED NAVAID	NAVIGATION SPECIFICATION
VA	-	-	326°	-	-	+1500	250	-	RNAV 1
DF	VLG VOR	-	-	-	L	-	-	-	RNAV 1

IDATU 1U

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY-OVER	Course/°M(°T)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT(KT)	RECOMMENDED NAVAID	NAVIGATION SPECIFICATION
VA	-	-	326°	-	-	+1500	250	-	RNAV 1
DF	IDATU	-	-	-	R	+7000	-	-	RNAV 1
TF	LATIL	-	108°	50	L	+11000	-	-	RNAV 1

NOLOT 1U

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY-OVER	Course/°M(°T)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT(KT)	RECOMMENDED NAVAID	NAVIGATION SPECIFICATION
VA	-	-	326°	-	-	+1500	250	-	RNAV 1
DF	NOLOT	-	-	-	L	+6000	-	-	RNAV 1
TF	VJN	-	052°	42	-	-	-	-	RNAV 1

WAYPOINT LIST

WAYPOINT IDENTIFIER	COORDINATES
NOLOT	05°27'55.70"N 115°28'53.71"N
IDATU	05°09'10.72"N 115°39'10.11"N
ESBOB	05°21'23.69"N 114°40'39.53"N
LAVED	05°20'25.08"N 114°50'36.08"N
BRU	04°52'28.52"N 114°53'07.77"E
VLG	04°47'50.20"N 115°00'08.40"N
VJN	05°53'57.30"N 116°02'02.30"N
LATIL	04°53'39.84"N 116°26'48.84"N

CHANGES : UPDATING THE CHART FORMAT.