

STANDARD ARRIVAL CHART
INSTRUMENT (STAR) - ICAO

LABUAN/LABUAN (WBKL)
ARRIVAL RWY 14 (RNAV 1)

TRANSITION ALTITUDE
11,000 FT

LAVED 1P
BRUNEI 1P
LIMBANG 1P

IDATU 1P
NOLOT 1P

TABULAR DESCRIPTION

LAVED 1P

SERIAL NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY-OVER	Course/ °M(°T)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT(KT)	RECOMMENDED NAVAID	TCH/ VPA	NAVIGATION SPECIFICATION
010	IF	ESBOB	-	-	-	-	+9000	250	-	-	RNAV 1
020	TF	LAVED	-	096°(95.6°)	10.0	-	+7000	250	-	-	RNAV 1
030	TF	DOKDU	-	064°(63.3°)	14.2	L	+3000	250	-	-	RNAV 1
040	TF	DAKBI	-	076°(75.6°)	5.0	-	+2000	220	-	-	RNAV 1

BRUNEI 1P

SERIAL NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY-OVER	Course/ °M(°T)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT(KT)	RECOMMENDED NAVAID	TCH/ VPA	NAVIGATION SPECIFICATION
010	IF	BRU	-	-	-	-	-	-	-	-	RNAV 1
020	TF	KAPLA	-	039°(38.8°)	26.4	-	+7000	250	-	-	RNAV 1
030	TF	DOKDU	-	335°(334.8°)	15.1	L	+3000	250	-	-	RNAV 1
040	TF	DAKBI	-	076°(75.6°)	5.0	R	+2000	220	-	-	RNAV 1

LIMBANG 1P

SERIAL NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY-OVER	Course/ °M(°T)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT(KT)	RECOMMENDED NAVAID	TCH/ VPA	NAVIGATION SPECIFICATION
010	IF	VLG	-	-	-	-	-	-	-	-	RNAV 1
020	TF	KAPLA	-	021°(21.0°)	26.9	-	+7000	250	-	-	RNAV 1
030	TF	DOKDU	-	335°(334.8°)	15.1	L	+3000	250	-	-	RNAV 1
040	TF	DAKBI	-	076°(75.6°)	5.0	R	+2000	220	-	-	RNAV 1

IDATU 1P

SERIAL NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY-OVER	Course/ °M(°T)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT(KT)	RECOMMENDED NAVAID	TCH/ VPA	NAVIGATION SPECIFICATION
010	IF	LATIL	-	-	-	-	-	-	-	-	RNAV 1
020	TF	IDATU	-	288°(288.0°)	50.0	-	+11000	-	-	-	RNAV 1
030	TF	IGNOP	-	305°(304.9°)	22.0	R	+7000	250	-	-	RNAV 1
040	TF	VASKA	-	316°(315.9°)	14.4	R	+3000	250	-	-	RNAV 1
050	TF	DAKBI	-	216°(215.6°)	5.0	L	+2000	220	-	-	RNAV 1

NOLOT 1P

SERIAL NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY-OVER	Course/ °M(°T)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT(KT)	RECOMMENDED NAVAID	TCH/ VPA	NAVIGATION SPECIFICATION
010	IF	VJN	-	-	-	-	-	250	-	-	RNAV 1
020	TF	NOLOT	-	232°(231.9°)	42.0	-	+8000	250	-	-	RNAV 1
030	TF	VASKA	-	284°(283.3°)	18.2	R	+3000	250	-	-	RNAV 1
040	TF	DAKBI	-	216°(215.6°)	5.0	L	+2000	220	-	-	RNAV 1

HOLDINGS

FIX ID	PATH TERMINATOR	FLY-OVER	Course/ °M(°T)	TIME (MIN)	TURN DIRECTION	MNM ALT (FT)	SPEED LIMIT(KT)	RECOMMENDED NAVAID	TCH/ VPA	NAVIGATION SPECIFICATION
KAPLA	HM	Y	335°	1	L	5500	220	-	-	RNAV 1
NOLOT	HM	Y	232°	1	R	5500	230	-	-	RNAV 1

CHANGES : UPDATING THE CHART FORMAT.