

STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO

TRANSITION ALTITUDE
11000 ft

KUANTAN/SULTAN AHMAD
SHAH (WMKD)
RNAV (GNSS) RWY 36
OSTIN 1C VPK 1C
MEVOK 1C OSIKU 1C
DAGAG 1C

TABULAR DESCRIPTION

OSTIN ONE CHARLIE DEPARTURE (OSTIN 1C)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KD251	-	003	9.6	-	+2500	-	-
TF	OSTIN	-	023	20.3	R	+4000	-	RNAV 1

MINIMUM CLIMB GRADIENT (PDG) OF 4.5% IS REQUIRED UNTIL KD251.

VPK ONE CHARLIE DEPARTURE (VPK 1C)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KD251	-	003	9.6	-	+2500	-	-
TF	KD252	-	093	8.0	R	-	-	RNAV 1
TF	KD253	-	159	18.7	R	-	-	RNAV 1
TF	VPK	-	189	15.8	R	+8000	-	RNAV 1

MINIMUM CLIMB GRADIENT (PDG) OF 4.5% IS REQUIRED UNTIL KD251.

MEVOK ONE CHARLIE DEPARTURE (MEVOK 1C)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KD251	-	003	9.6	-	+2500	-	-
TF	KD254	-	273	8.0	L	-	-	RNAV 1
TF	KD255	-	242	9.5	L	-	-	RNAV 1
TF	MEVOK	-	200	25.3	L	+7000	-	RNAV 1

MINIMUM CLIMB GRADIENT (PDG) OF 4.5% IS REQUIRED UNTIL KD251.

OSIKU ONE CHARLIE DEPARTURE (OSIKU 1C)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KD251	-	003	9.6	-	+2500	-	-
TF	KD254	-	273	8.0	L	-	-	RNAV 1
TF	KD255	-	242	9.5	L	-	-	RNAV 1
TF	OSIKU	-	242	16.2	-	+9500	-	RNAV 1

MINIMUM CLIMB GRADIENT (PDG) OF 4.5% IS REQUIRED UNTIL KD251.

NEW TABULAR