

STANDARD ARRIVAL CHART INSTRUMENT (STAR) - ICAO

TRANSITION ALTITUDE
11000 FT

SEPANG/KL INTERNATIONAL AIRPORT (WMKK) RNAV (GNSS) RWY 32R, 32L, 33, 14L, 14R, 15

PUGER 1G
NIREN 1G

KAKAK 1G
PULIP 1G

PMS EAST
SAROX 1G
GUPTA 1G
SALAX 1G

KAKAK ONE GOLF ARRIVAL (KAKAK 1G)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	KAKAK	-	-	-	-	-	-	-	RNP 1
TF	LIBKI	-	133	-	43.7	-	-	-	RNP 1
TF	RITLO	-	129	-	12.5	-	+FL180	@250	RNP 1
TF	KK811	-	109	-	4.4	L	-	-	RNP 1
TF	KK812	-	124	-	4.4	R	-	-	RNP 1
TF	KK813	-	139	-	4.4	R	-	-	RNP 1
TF	KK814	-	154	-	4.4	R	-	-	RNP 1
TF	KK815	-	169	-	4.4	R	-	-	RNP 1
TF	KK816	-	184	-	4.4	R	-	@250	RNP 1
TF	EGURI	-	281	-	17.0	R	+FL130	@230	RNP 1

PULIP ONE GOLF ARRIVAL (PULIP 1G)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	PULIP	-	-	-	-	-	-	-	RNP 1
TF	LIBKI	-	199	-	25.4	-	-	-	RNP 1
TF	RITLO	-	129	-	12.5	L	+FL180	@250	RNP 1
TF	KK811	-	109	-	4.4	L	-	-	RNP 1
TF	KK812	-	124	-	4.4	R	-	-	RNP 1
TF	KK813	-	139	-	4.4	R	-	-	RNP 1
TF	KK814	-	154	-	4.4	R	-	-	RNP 1
TF	KK815	-	169	-	4.4	R	-	-	RNP 1
TF	KK816	-	184	-	4.4	R	-	@250	RNP 1
TF	EGURI	-	281	-	17.0	R	+FL130	@230	RNP 1

SAROX ONE GOLF ARRIVAL (SAROX 1G)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	SAROX	-	-	-	-	-	-	-	RNP 1
TF	VEKTO	-	256	-	25.5	-	-FL170	-	RNP 1
TF	NUKPA	-	316	-	8.4	R	-FL170	@250	RNP 1
TF	KK804	-	004	-	4.7	R	-	-	RNP 1
TF	KK805	-	349	-	4.7	L	-	-	RNP 1
TF	KK806	-	334	-	4.7	L	-	-	RNP 1
TF	KK807	-	319	-	4.7	L	-	-	RNP 1
TF	KK808	-	304	-	4.7	L	-	-	RNP 1
TF	KK809	-	289	-	4.7	L	-	@250	RNP 1
TF	EGURI	-	191	-	18.0	L	+FL130	@230	RNP 1

CHANGES: CHANGE TURN DIRECTION FOR RITLO.