

**STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO**TRANSITION ALTITUDE
11 000 FT**SEPANG/KL INTERNATIONAL
AIRPORT (WMKK)
RNP 1 (GNSS) RWY 33**PUGER 1F BIKDU 1F SALAX 1F
IBUKU 1F PIBOS 1F MITOS 1F
ATIMU 1F KIMAT 3F RUSBU 1F**PIBOS ONE FOXTROT DEPARTURE (PIBOS 1F)**

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK715	Y	326	-	1.1	-	+430	-	RNP 1
DF	KK716	-	-	-	-	L	-	-	RNP 1
TF	KK717	-	168	-	5.0	L	-	-	RNP 1
TF	KK718	-	084	-	6.1	L	+6000	-	RNP 1
TF	KK706	-	014	-	16.3	L	-	-	RNP 1
TF	KK705	-	014	-	13.1	-	-	-	RNP 1
TF	MAGIB	-	056	-	10.4	R	-	-	RNP 1
TF	PIBOS	-	054	-	8.5	-	-	-	RNP 1

KIMAT THREE FOXTROT DEPARTURE (KIMAT 3F)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK715	Y	326	-	1.1	-	+430	-	RNP 1
DF	KK716	-	-	-	-	L	-	-	RNP 1
TF	KK717	-	168	-	5.0	L	-	-	RNP 1
TF	KK718	-	084	-	6.1	L	+6000	-	RNP 1
TF	KK706	-	014	-	16.3	L	-	-	RNP 1
TF	KK705	-	014	-	13.1	-	-	-	RNP 1
TF	MAGIB	-	056	-	10.4	R	-	-	RNP 1
TF	KIMAT	-	104	-	25.4	R	-	-	RNP 1

RUSBU ONE FOXTROT DEPARTURE (RUSBU 1F)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
CF	KK715	Y	326	-	1.1	-	+430	-	RNP 1
DF	KK716	-	-	-	-	L	-	-	RNP 1
TF	KK717	-	168	-	5.0	L	-	-	RNP 1
TF	KK712	-	180	-	3.0	-	-	-	RNP 1
TF	IDUMI	-	160	-	17.3	L	-	-	RNP 1
TF	OMBIR	-	135	-	26.7	L	-	-	RNP 1
TF	RUSBU	-	093	-	31.1	L	-	-	RNP 1

CHANGES : REPLACEMENT CHART