

**STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO**

TRANSITION ALTITUDE
11000 FT

**SIBU/SIBU (WBGS)
RNAV (GNSS) RWY 13**
NOLUS 1A REDUK 1A LENTU 1A
ELNAL 1A BIPIB 1A ANKUP 1A
PILAX 1A

TABULAR DESCRIPTIONS

NOLUS ONE ALFA DEPARTURE (NOLUS 1A)

PATH TERMINATOR	WAYPOINT	FLY OVER	COURSE/TRACK (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	RECOMMENDED NAVAIDS	NAVIGATION SPECIFICATION
CA	-	-	130°	-	-	+2000	-	-	RNAV 1
DF	NOLUS	-	-	-	L	+5000	-	-	RNAV 1

REDUK ONE ALFA DEPARTURE (REDUK 1A)

PATH TERMINATOR	WAYPOINT	FLY OVER	COURSE/TRACK (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	RECOMMENDED NAVAIDS	NAVIGATION SPECIFICATION
CA	-	-	130°	-	-	+2000	-	-	RNAV 1
DF	TAMIG	-	-	-	L	-	-	-	RNAV 1
TF	REDUK	-	049°	13.1	R	+7000	-	-	RNAV 1

LENTU ONE ALFA DEPARTURE (LENTU 1A)

PATH TERMINATOR	WAYPOINT	FLY OVER	COURSE/TRACK (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	RECOMMENDED NAVAIDS	NAVIGATION SPECIFICATION
CA	-	-	130°	-	-	+2000	-	-	RNAV 1
DF	APPAD	-	-	-	L	-	-	-	RNAV 1
TF	LENTU	-	068°	10.0	R	+7000	-	-	RNAV 1

ELNAL ONE ALFA DEPARTURE (ELNAL 1A)

PATH TERMINATOR	WAYPOINT	FLY OVER	COURSE/TRACK (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	RECOMMENDED NAVAIDS	NAVIGATION SPECIFICATION
CA	-	-	130°	-	-	+2000	-	-	RNAV 1
DF	TULMA	-	-	-	R	-	-	-	RNAV 1
TF	ELNAL	-	225°	10.0	L	+7000	-	-	RNAV 1

BIPIB ONE ALFA DEPARTURE (BIPIB 1A)

PATH TERMINATOR	WAYPOINT	FLY OVER	COURSE/TRACK (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	RECOMMENDED NAVAIDS	NAVIGATION SPECIFICATION
CA	-	-	130°	-	-	+2000	-	-	RNAV 1
DF	MEGOX	-	-	-	R	-	-	-	RNAV 1
TF	BIPIB	-	247°	10.0	L	+7000	-	-	RNAV 1

NEW TABULAR