

**STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO**

TRANSITION ALTITUDE 11000 FT

**SIBU/SIBU (WBGS)
RNAV (GNSS) RWY 31**
NOLUS 1C REDUK 1C LENTU 1C
ELNAL 1C BIPIB 1C ANKUP 1C
PILAX 1C

TABULAR DESCRIPTIONS

NOLUS ONE CHARLIE DEPARTURE (NOLUS 1C)

PATH TERMINATOR	WAYPOINT	FLY OVER	COURSE/TRACK (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	RECOMMENDED NAVAIDS	NAVIGATION SPECIFICATION
CA	-	-	310°	-	-	+2000	-	-	RNAV 1
DF	NOLUS	-	-	-	R	+5000	-	-	RNAV 1

REDUK ONE CHARLIE DEPARTURE (REDUK 1C)

PATH TERMINATOR	WAYPOINT	FLY OVER	COURSE/TRACK (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	RECOMMENDED NAVAIDS	NAVIGATION SPECIFICATION
CA	-	-	310°	-	-	+2000	-	-	RNAV 1
DF	TAMIG	-	-	-	R	-	-	-	RNAV 1
TF	REDUK	-	049°	13.1	L	+7000	-	-	RNAV 1

LENTU ONE CHARLIE DEPARTURE (LENTU 1C)

PATH TERMINATOR	WAYPOINT	FLY OVER	COURSE/TRACK (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	RECOMMENDED NAVAIDS	NAVIGATION SPECIFICATION
CA	-	-	310°	-	-	+2000	-	-	RNAV 1
DF	APPAD	-	-	-	R	-	-	-	RNAV 1
TF	LENTU	-	068°	10.0	L	+7000	-	-	RNAV 1

ELNAL ONE CHARLIE DEPARTURE (ELNAL 1C)

PATH TERMINATOR	WAYPOINT	FLY OVER	COURSE/TRACK (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	RECOMMENDED NAVAIDS	NAVIGATION SPECIFICATION
CA	-	-	310°	-	-	+2000	-	-	RNAV 1
DF	TULMA	-	-	-	L	-	-	-	RNAV 1
TF	ELNAL	-	225°	10.0	R	+7000	-	-	RNAV 1

BIPIB ONE CHARLIE DEPARTURE (BIPIB 1C)

PATH TERMINATOR	WAYPOINT	FLY OVER	COURSE/TRACK (°M)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE CONSTRAINT	SPEED LIMIT (KT)	RECOMMENDED NAVAIDS	NAVIGATION SPECIFICATION
CA	-	-	310°	-	-	+2000	-	-	RNAV 1
DF	MEGOX	-	-	-	L	-	-	-	RNAV 1
TF	BIPIB	-	247°	10.0	R	+7000	-	-	RNAV 1

NEW TABULAR