

**STANDARD ARRIVAL CHART
INSTRUMENT (STAR) - ICAO**

TRANSITION ALTITUDE
11000 FT

**SEPANG/KL INTERNATIONAL
AIRPORT (WMKK)**

**RNAV (GNSS) RWY 32R, 32L, 33,
14L, 14R, 15**

PUGER 1G KAKAK 1G PMS EAST
NIREN 1G PULIP 1G SAROX 1G
GUPTA 1G
SALAX 1G

GUPTA ONE GOLF ARRIVAL (GUPTA 1G)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	GUPTA	-	-	-	-	-	-	-	RNP 1
TF	KK802	-	333	-	23.4	-	-	-	RNP 1
TF	KK803	-	313	-	5.1	L	-	-	RNP 1
TF	VEKTO	-	313	-	11.6	-	-FL170	-	RNP 1
TF	NUKPA	-	316	-	8.4	-	-FL170	@250	RNP 1
TF	KK804	-	004	-	4.7	R	-	-	RNP 1
TF	KK805	-	349	-	4.7	L	-	-	RNP 1
TF	KK806	-	334	-	4.7	L	-	-	RNP 1
TF	KK807	-	319	-	4.7	L	-	-	RNP 1
TF	KK808	-	304	-	4.7	L	-	-	RNP 1
TF	KK809	-	289	-	4.7	L	-	@250	RNP 1
TF	EGURI	-	191	-	18.0	L	+FL130	@230	RNP 1

SALAX ONE GOLF ARRIVAL (SALAX 1G)

PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY OVER	COURSE °M	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED LIMIT (KT)	NAVIGATION SPECIFICATION
IF	SALAX	-	-	-	-	-	-	-	RNP 1
TF	KK801	-	107	-	5.1	-	-	-	RNP 1
TF	KK803	-	063	-	51.1	L	-	-	RNP 1
TF	VEKTO	-	313	-	11.6	L	-FL170	-	RNP 1
TF	NUKPA	-	316	-	8.4	-	-FL170	@250	RNP 1
TF	KK804	-	004	-	4.7	R	-	-	RNP 1
TF	KK805	-	349	-	4.7	L	-	-	RNP 1
TF	KK806	-	334	-	4.7	L	-	-	RNP 1
TF	KK807	-	319	-	4.7	L	-	-	RNP 1
TF	KK808	-	304	-	4.7	L	-	-	RNP 1
TF	KK809	-	289	-	4.7	L	-	@250	RNP 1
TF	EGURI	-	191	-	18.0	L	+FL130	@230	RNP 1