

STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO

TRANSITION ALTITUDE
11,000 FT

KOTA KINABALU/KOTA KINABALU (WBKK)
RWY 02
DEPARTURES (LEFT TURN)
(RNAV 1)

TABULAR DESCRIPTION

ROUTE DESIGNATOR	SERIAL NUMBER	PATH DESCRIPTOR	WP IDENTIFIER	FLY OVER	COURSE/ °(T)	MAGNETIC VARIATION	DISTANCE (NM)	TURN DIRECTION	ALTITUDE (FT)	SPEED (KT) IAS MAX	RECOMMENDED NAVAID	NAVIGATION SPECIFICATION
ADLEX 1F	010	CA	-	-	022°	-	-	-	+1500	205	VJN DVOR/DME	RNAV 1
	020	DF	BITON	-	-	-	-	L	+4000	-	-	RNAV 1
	030	TF	UKALO	-	258°	-	12	R	-	-	-	RNAV 1
	040	TF	ADLEX	-	261°	-	30.7	R	-	-	-	RNAV 1
-	010	CA	-	-	022°	-	-	-	+1500	205	VJN DVOR/DME	RNAV 1
	020	DF	BITON	-	-	-	-	L	+4000	-	-	RNAV 1
	030	TF	UKALO	-	258°	-	12	-	-	-	-	RNAV 1
	040	TF	EGENU	-	236°	-	27	L	-	-	-	RNAV 1
SUKUS 1F	010	CA	-	-	022°	-	-	-	+1500	205	VJN DVOR/DME	RNAV 1
	020	DF	BITON	-	-	-	-	L	+4000	-	-	RNAV 1
	030	TF	UKBON	-	206°	-	20	L	-	-	-	RNAV 1
	040	TF	KILOB	-	206°	-	12	-	-	-	-	RNAV 1
	050	TF	SUKUS	-	249°	-	13	R	-	-	-	RNAV 1
DULIM 2F	010	CA	-	-	022°	-	-	-	+1500	205	VJN DVOR/DME	RNAV 1
	020	DF	BITON	-	-	-	-	L	+4000	-	-	RNAV 1
	030	TF	UKBON	-	206°	-	20	L	-	-	-	RNAV 1
	040	TF	KILOB	-	206°	-	12	-	-	-	-	RNAV 1
	050	TF	DULIM	-	237°	-	13	R	-	-	-	RNAV 1
OREKO 1F	010	CA	-	-	022°	-	-	-	+1500	205	VJN DVOR/DME	RNAV 1
	020	DF	BITON	-	-	-	-	L	+4000	-	-	RNAV 1
	030	TF	UKBON	-	206°	-	20	L	-	-	-	RNAV 1
	040	TF	KILOB	-	206°	-	12	-	-	-	-	RNAV 1
	050	TF	OREKO	-	222°	-	12.5	R	-	-	-	RNAV 1
PIMEP 2F	010	CA	-	-	022°	-	-	-	+1500	205	VJN DVOR/DME	RNAV 1
	020	DF	BITON	-	-	-	-	L	+4000	-	-	RNAV 1
	030	TF	UKBON	-	206°	-	20	L	-	-	-	RNAV 1
	040	TF	KILOB	-	206°	-	12	-	-	-	-	RNAV 1
	050	TF	PIMEP	-	205°	-	13	-	-	-	-	RNAV 1
ELADO 2F	010	CA	-	-	022°	-	-	-	+1500	205	VJN DVOR/DME	RNAV 1
	020	DF	BITON	-	-	-	-	L	+4000	-	-	RNAV 1
	030	TF	UKBON	-	206°	-	20	-	-	-	-	RNAV 1
	040	TF	DOVID	-	165°	-	12	L	-	-	-	RNAV 1
	050	TF	ELADO	-	165°	-	19.6	-	-	-	-	RNAV 1
NOTE : INITIAL CLIMB AT 5% MNM GR.ON RWY HDG TILL 1500 FT; TURN LEFT CONTINUE AT 5% MNM PDG UNTIL BITON. RESUME NORMAL CLIMB THEREAFTER.												
ANLOD 2F	010	CA	-	-	022°	-	-	-	+1500	205	VJN DVOR/DME	RNAV 1
	020	DF	BITON	-	-	-	-	L	+4000	-	-	RNAV 1
	030	TF	VJN	-	151°	-	10.2	L	+7000	-	-	RNAV 1
	040	TF	TOMEL	-	110°	-	10	L	+9000	-	-	RNAV 1
	050	TF	ANLOD	-	084°	-	30.8	L	+FL170	-	-	RNAV 1

CHANGES : UPDATING THE CHART FORMAT